

USER SYMBOLS:
NAVY - MC

REVIEWER SYMBOLS:
NAVY - SH, EC
USAF - 11, 99
ARMY - AV

"Review/user information is current as of the date of this document.
For future coordination of changes to this document, draft circulation
should be based on the information in the current DODISS."

This military standard is approved for use by all Departments
& Agencies of the Department of Defense. Selection for all new
engineering and design applications and for repetitive use shall
be made from this document.

DESIGN OPTIONAL														FED. SUP CLASS 5940	

FED. SUP CLASS

5940

(B)

INCHES	mm	INCHES	mm
.010	0.25	.187	4.75
.015	0.38	.190	4.83
.023	0.58	.192	4.88
.032	0.81	.250	6.35
.037	0.94	.302	7.67
.046	1.17	.322	8.18
.052	1.32	.343	8.71
.062	1.58	1.000	25.40
.070	1.78	1.248	31.70
.081	2.06	1.311	33.30
.090	2.29	1.436	36.47
.110	2.54	1.500	38.10
.128	3.25	2.000	50.80
.135	3.43	2.500	63.50
.139	3.53	3.000	76.20
.165	4.19	4.000	101.60
.168	4.26	6.000	152.40
.178	4.52	9.000	228.60

USER SYMBOLS:
NAVY - MC

REVIEWER SYMBOLS:
NAVY - SH, EC
USAF - 1199
ARMY - AY

"Review/user information is current as of the date of this document.
For future coordination of changes to this document, draft circulation
should be based on the information in the current DODISS."

This military standard is mandatory for use by all Departments
B. Agencies of the Department of Defense. Selection for all new
engineering and design applications and for repetitive use shall
be made from this document.

APPROVED 26 SEPT 67 REVISED (B) FOR CHANGES SEE SHEETS 1 AND 2

P.A. NAVY - AS Other Cust Army - ER USAF - 85	TITLE TERMINAL, LUG, UNINSULATED, RECTANGULAR TONGUE LIPPED END, CRIMP STYLE, TYPE I, CLASS 1, FOR 175°C TOTAL CONDUCTOR TEMPERATURE	MILITARY STANDARD MS 21010
ACQUISITION SPECIFICATION MIL-T-7928	SUPERSEDES:	SHEET 2 OF 2

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 17709