


FED. SUP CLASS
5340



DASH NO.	(a) A	B	C +.010 -.015	D	F	G	H	R RAD
-1	.965	1.115		1.078		.300	.165	
-2	1.875	2.000	.150	1.955	.125	.315	.180	.032
-3	2.045	2.140	.215	2.015	.150	.430	.275	

(a) DIMENSION A MUST BE HELD WITHOUT DISTORTION AT END.

MATERIAL: CORROSION RESISTANT STEEL WIRE, QQ-W-423, COMPOSITION FS302, CONDITION B.
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm .015$. UNLESS OTHERWISE SPECIFIED, ALL INTERNAL RADII $.032 \pm .000, -.015$.

FOR LOCK CLIPPING OF AIRCRAFT TURNBUCKLES, SEE MS33736.
ENDS OF LOCKING CLIP SHALL BE CUT SQUARE AND SHALL BE FREE OF BURRS.

Ⓒ LOCKING CLIPS ARE FOR ONE TIME USE ONLY AND SHALL NOT BE REUSED.

Ⓒ REVISED AND REDRAWN

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

P. A. AF-82 Other Cust NAVY - AS ARMY - AV AF - 99	Ⓒ INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
		CLIP, LOCKING, TURNBUCKLE	MS 21256
PROCUREMENT SPECIFICATION MIL-T-8878	SUPERSEDES:	SHEET OF	

USER ACTIVITY: NAVY - MC

REVIEW ACTIVITY: DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED | NOV 61 | REVISED | A | 1 JUN 62 | B | 25 NOV 63 | C | 1 AUG 61 | 83