

MS21260M

TABLE I. Dash numbers and dimensions.

Dash number		Wire rope diameter		Minimum breaking strength lb <u>1</u> /	Thread B UN-3A UNF-3A	ØA		ØAs	
		Nominal reference	Minimum						
RH thread	LH thread								
L2RH	L2LH	1/16	.062	480	.1380 (# 6)-40	.160	+ .000 - .005	.138	+ .000 - .005
S2RH	S2LH							.190	
L3RH	L3LH							.219	
S3RH	S3LH	3/32	.093	920	.1900 (#10)-32	.218		.250	
L4RH	L4LH							.313	
S4RH	S4LH							.375	
L5RH	L5LH	1/8	.125	2000	.2500 (1/4)-28	.250		.438	+ .000 - .007
S5RH	S5LH							.500	
L6RH	L6LH							.563	
S6RH	S6LH	5/32	.156	2800	.3125 (5/16)-24	.297		.625	
-7RH	-7LH							.688	
-8RH	-8LH							.750	
-9RH	-9LH	7/32	.218	5600	.3750 (3/8)-24	.427	+ .000 - .010	.875	
-10RH	-10LH	1/4	.250	7000		.494		1.000	
-12RH	-12LH	9/32	.281	8000	.4375 (7/16)-20	.563		1.250	
-14RH	-14LH	5/16	.312	9800		.635		1.437	
-16RH	-16LH	3/8	.375	14400	.5625 (9/16)-18	.703		1.625	+ .000 - .012
-18RH	-18LH	7/16	.437	17600		.781		1.812	
-20RH	-20LH	1/2	.500	22800	.6250 (5/8)-18	.844		2.000	
-24RH	-24LH	9/16	.562	28500		.984		2.250	
-28RH	-28LH	5/8	.625	35000	.8750 (7/8)-14	1.109		2.500	
-32RH	-32LH	3/4	.750	49600		1.359		2.750	
-36RH	-36LH	7/8	.875	66500	1.1250 (1 1/8)-12	1.593	+ .000 - .010	3.000	+ .000 - .012
-40RH	-40LH	1	1.000	85400		1.812		3.250	

1/ To achieve the minimum breaking strength, for the terminal test only, a galvanized carbon steel wire rope shall be used.

TABLE I. Dash numbers and dimensions - Continued.

Dash number		B ₁		ØC +.006 -.000	D	E +.000 -.010	ØF	G		H		
RH thread	RH thread							Maximum	Minimum	Maximum	Minimum	
L2RH	L2LH	1.042	±.063	.092	.188	.156	.188.	.1139	.1094	.031	.015	
S2RH	S2LH			.133	.250	.187	.250	.1638	.1568			
L3RH	L3LH	1.261		.195	.313	.250	.313	.2224	.2152	.047		
S3RH	S3LH											.245
L4RH	L4LH	1.511		.306	.438	.375	.438	.3454	.3378			
S4RH	S4LH											.500
L5RH	L5LH	1.761		.361	.625	.563	.625	.4052	.4072		.063	
S5RH	S5LH											.406
L6RH	L6LH	2.011		.476	.750	.688	.750	.5285	.5201	.031		
S6RH	S6LH											.538
-7RH	-7LH	2.261		.654	1.000	.875	1.000	.7137	.7050			.078
-8RH	-8LH	2.511										
-9RH	-9LH	2.761		.893	1.438	1.125	1.438	.9608	.9516		.048	
-10RH	-10LH	3.011										
-12RH	-12LH	3.511		1.002	1.625	1.438	1.625	1.0819	1.0772	.094		
-14RH	-14LH	4.011										
-16RH	-16LH	4.698		1.128	1.875	1.625	1.812	1.2069	1.1972			.062
-18RH	-18LH	5.011										
-20RH	-20LH	5.511		1.128	1.875	1.625	1.812	1.2069	1.1972		.062	
-24RH	-24LH	6.511										
-28RH	-28LH	7.166		1.128	1.875	1.625	1.812	1.2069	1.1972	.062		
-32RH	-32LH	8.229										

MS21260M

TABLE I. Dash numbers and dimensions - Continued.

Dash number	L ±.063	Ls reference	ØM		ØN		P		Q +.031 -.016	S +.062 -.000	ØT	
L2	3.491	3.67	.090	+.010 -.000	.078	+.005 -.000	1.042	+.031 -.000	1.319	.969	.138	+.000 -.005
S2	2.616	2.79										
L3	3.738	3.86	.119		.109		1.261		1.581	1.188	.190	
S3	2.863	2.98										
L4	4.020	4.28	.154		.141		1.511		1.863	1.438	.219	
S4	3.145	3.40										
L5	4.314	4.66	.188		.172		1.761		2.157	1.688	.250	
S5	3.439	3.78										
L6	4.612	4.78	.223		.203		2.011		2.455	1.938	.313	
S6	3.737	3.90										
-7	4.914	5.21	.257	.234	2.261	2.757	2.188	.375	+.000 -.007			
-8	5.218	5.52	.291	.265	2.511	3.061	2.438	.438				
-9	5.542	5.90	.326	.297	2.761	3.385	2.688	.500	+.000 -.008			
-10	5.875	6.30	.360	.328	3.011	3.718	2.938	.563				
-12	6.608	7.01	.430	+.012 -.000	.390	+.008 -.000	3.511	+.047 -.000	4.281	3.438	.625	+.000 -.009 +.000 -.010
-14	7.468	7.94	.514		.468		4.011		4.812	3.938	.688	
-16	8.718	9.28	.584		.531	4.698	5.562	4.625	.750			
-18	9.188	9.78	.653		.594	5.011	6.000	4.938	.875			
-20	10.469	11.16	.722		.656	5.511	6.750	5.438	1.000			
-24	12.188	12.76	.860	+.015 -.000	.781	+.012 -.000	6.511	+.062 -.000	7.938	6.438	1.250	+.000 -.012
-28	12.851	13.61	1.013		.921		7.166		8.601	7.094	1.437	
-32	14.624	15.53	1.151		1.046		8.229		9.844	8.156	1.625	

TABLE I. Dash numbers and dimensions - Continued.

Dash number	ØU reference	ØV ±.005	W ±.016	X	Y ±.047 2/	Z	ØBB	
				Minimum		Minimum		
L2	.094	.063	1.174	.70	.375	.03	008 (.016 FIM)	
S2								
L3			1.411	.80	.500			
S3								
L4	.125	.098	1.682	1.05	.563			
S4								
L5			1.958	1.29	.625			
S5								
L6			2.237	1.31	.750			
S6								
-7			2.518	1.55	.875			
-8			2.784	1.70				
-9			3.076	1.89	1.000			
-10			3.326	2.06				
-12			3.828	3.12	1.125			
-14			4.375	3.57	1.250			
-16	5.093	4.31						
-18	.188	.125	5.468	4.51	1.500	.010 (.020 FIM)		
-20			6.093	5.04	1.750			
-24			7.188	5.80	2.000	.015 (.030 FIM)		
-28			7.846	6.31				
-32			9.000	7.26	2.250	.020 (.040 FIM)		

2/ Includes last full thread engagement.

MS21260M

REQUIREMENTS:

1. Material: Material shall be in accordance with MIL-DTL-781
2. Finish: Finish shall be in accordance with MIL-DTL-781.
3. Threads: Threads shall be in accordance with FED-STD-H28/20.
4. Swage: Swage shall be in accordance with MIL-DTL-6117.
5. Tolerances: Unless otherwise specified, tolerances: decimals $\pm .010$, angles $\pm 3^\circ$.

NOTES:

* 1. The part or identifying number (PIN) consists of the letters MS, the specification sheet
 * number and a dash number taken from table I. An "L" in lieu of dash indicates long; an "S" in
 * lieu of a dash indicates short. The two letters following the dash number or letters "L" or "R"
 * indicates direction of thread (left or right hand).

EXAMPLE: MS 21260 - 7RH

Dash number

Use "L" for long
or "S" for short

Specification sheet number

MS prefix

MS21260L2RH Indicates - Terminal, .1380 (#6)-40 right hand thread, long.
 MS21260-7RH Indicates- Terminal, .3750 (3/8)-24 right hand thread.

2. Dimensions are in inches.
- * 3. Remove burrs and sharp edges. (See MIL-DTL-781.)
4. Interpret drawing in accordance with ASME Y14.5M.
5. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence.
6. Unless otherwise specified, issues of reference documents are those in effect at the time of solicitation.
7. Interchangeability relationship: MS21260 parts can universally replace the canceled AN669 and NAS650 parts identified by the same dash number; but the canceled

MS21260M

AN669 and NAS650 parts cannot replace the superseding MS21260 parts. MS21260 corrosion resistant steel parts can universally replace the canceled carbon and alloy steel parts identified by the same dash number.

8. Carbon and alloy steel parts are inactive for new design.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - AR
Navy - AS
Air Force - 99

Preparing activity:

DLA - GS5

(Project 1560-0011)

Reviewers:

Army - CR4
Navy - MC
Air Force - 71