


FED. SUP CLASS
5340

NOTES:

1. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
2. THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
3. MATERIAL - STEEL, SHALL BE IN ACCORDANCE WITH FEDERAL SPECIFICATION QQ-S-633.
4. HOOK SHALL BE HOT DIP GALVANIZED IN ACCORDANCE WITH MILITARY SPECIFICATION MIL-Z-17871.
5. ALL METAL PARTS SHALL BE FREE FROM CHIPS, BURRS, AND SCRATCHES IN ACCORDANCE WITH GOOD COMMERCIAL PRACTICE.
6. SCREW THREAD SHALL BE IN ACCORDANCE WITH FEDERAL SPECIFICATION FF-B-561.
7. HOOK SHALL BEAR THE MANUFACTURER'S SYMBOL OR IDENTIFICATION MARK IN ACCORDANCE WITH FEDERAL SUPPLY CODE FOR MANUFACTURERS.

ALL DIMENSIONS IN INCHES

P.A. EL Other Cust YD 69	TITLE BOLT, HOOK, SUPPORT, DRIVE FETTER THREAD (POLE LINE)	MILITARY STANDARD MS 21310
PROCUREMENT SPECIFICATION MIL-R-55053	SUPERSEDES:	

5340-Q26L

Reviewers/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on information in current DOLISS(FSC listing).

ARMY: GLE W. EL. NAVY: WJG SA. YDG AIR FORCE: 268 69. 85+

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 16 JULY 58 REVISED (A2) 10 11 12 13 14