

TABLE I. DASH NUMBERS AND DIMENSIONS.

DASH NO.	PIPE OR CONDUIT SIZE	CABLE O.D.	A ±.010	B ±.010	C +.125 -.000	D ±.062	ØE +.031 -.016	F ±.125	G ±.015	R ±.125		
1	1/8	13/32	.406	.203	.500	.219	.203	1.750	.048	.375		
2	1/4	17/32	.540	.270								
3		9/16	.562	.281			.219	2.000				
4		5/8	.625	.312								
5	3/8	11/16	.688	.344	.625	.375	.281	2.375	.063	.500		
6		3/4	.750	.375	.688			2.500				
7	1/2	27/32	.844	.422	.750			2.625				
8		1	1.000	.500				2.750				
9	3/4	1-1/16	1.062	.531				2.875	.080	.562		
10		1-1/8	1.125	.562				3.000				
11	1	1-5/16	1.315	.657	.875			3.125				
12		1-1/2	1.500	.750				3.375				
13	1-1/4	1-21/32	1.660	.830				3.625	.125	.625		
14		1-3/4	1.750	.875				3.750				
15	1-1/2	1-29/32	1.906	.953	1.000	.500	.344	4.000				
16	2	2-3/8	2.375	1.187				5.500				
17	2-1/2	2-7/8	2.875	1.437				6.000	.750			
18	3	3-1/2	3.500	1.750				6.500				
19	3-1/2	4	4.000	2.000	1.125	.600	.375	7.000	.187	.813		
20	4	4-1/2	4.500	2.250			.437	7.250				

(B) ENTIRE STANDARD REVISED

INCH - POUND

PREPARING ACTIVITY: AR

CUSTODIANS: ARMY-

NAVY- YD

AIR FORCE- 99

DLA-

REVIEW: MI,IS

USER: ER,ME,MC

PROJECT NUMBER: 5340-2074

MILITARY SPECIFICATION SHEET

TITLE

STRAP, RETAINING, TWO HOLE, FOR
PIPE, CONDUIT, AND CABLE

SPECIFICATION SHEET NUMBER

MS21314B 30 DEC 91

SUPERSEDING (SEE NOTE 3)
MS21314A 22 MARCH 1966

AMSC- N/A

FSC- 5340

DISTRIBUTION STATEMENT


A Approved for public release; distribution is unlimited.

Page 1 of 2

REQUIREMENTS:

1. **MATERIAL:** STEEL, CARBON, SHEET OR STRIP IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
2. **PROTECTIVE COATING:** CADMIUM PLATED, IN ACCORDANCE WITH QQ-P-416, CLASS 1, TYPE II; ZINC COATED IN ACCORDANCE WITH ASTM B 633, TYPE II, Fe/Zn 13.
3. STRAP SHALL BE FREE OF BURRS AND SHARP EDGES, .010 RADIUS MAXIMUM.
4. **PART NUMBER:** THE PART NUMBER SHALL CONSIST OF THE BASIC MS SHEET NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

Example: MS21314-8



MS21314-8 INDICATES - STRAP, RETAINING, TWO HOLE, A DIMENSION 1.000, B DIMENSION .500
CADMIUM PLATED OR ZINC COATED.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
2. STRAP CORRESPONDS TO Type II, STYLE A, PIPE, CONDUIT OR CABLE IN ACCORDANCE WITH PROCUREMENT SPECIFICATION.
3. MS21314 SUPERSEDES BLAX.1.
4. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE
5. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION, FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

PREPARING ACTIVITY: AR
CUSTODIANS: ARMY- NAVY- YD
AIR FORCE- 99 DLA-
REVIEW: M.I.S
USER: ER,ME,MC
PROJECT NUMBER: 5340-2074

MILITARY SPECIFICATION SHEET
TITLE
STRAP, RETAINING, TWO HOLE, FOR
PIPE, CONDUIT, AND CABLE

SPECIFICATION SHEET NUMBER

MS21314B 30 DEC 91SUPERSEDING (SEE NOTE 3)
MS21314A 22 MARCH 1966

AMSC- N/A FSC - 5340

DISTRIBUTION STATEMENT

A. Approved for public release; distribution is unlimited.

Page 2 of 2