



DASH NO	A ± .015	B	C ± .015	D ± .015
-1	.406	.105	.109	.094
-2	.578	.075	.313	.094
-3	.453	.156	.125	.094
-4	.375	.062	.125	.094
-5	.359	.075	.094	.078

NOTES

1. MATERIAL: CORROSION RESISTANT STEEL, SPECIFICATION QQ-S-763, CLASS 303 OR 410.
2. FINISH: BREAK SHARP EDGES AND REMOVE ALL BURRS. PASSIVATE IN ACCORDANCE WITH QQ-P-35.
3. DIMENSIONS: ALL DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm .002$, ANGLES $\pm 2^\circ$.
4. PART NUMBER: THE MS PART NO CONSISTS OF THE MS NUMBER PLUS THE DASH NUMBER, EXAMPLE: MS21325-1.
5. USED WITH: FASTENER-SNAPSLIDE, MS 21332.
6. THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
7. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS TO BID.
8. ~~INTERCHANGEABILITY RELATION WITH AN3198 STUDS: MS21325 STUDS AND AN3198 STUDS OF LIKE DASH NUMBERS ARE UNIVERSALLY, FUNCTIONALLY AND DIMENSIONALLY INTERCHANGEABLE.~~

U.S. GOVERNMENT PRINTING OFFICE: 1983-605-034-519

P.A. AIR FORCE-82 (B) Other Cust	TITLE STUD - STYLE III SNAPSLIDE FASTENER	MILITARY STANDARD MS 21325
ARMY - GL NAVY - AS AIR FORCE - 99	SUPERSEDES: AN3198	SHEET 1 OF 1
PROCUREMENT SPECIFICATION NONE		