



FED. SUP CLASS
5950Review Activity:
AF - 99

INCHES	MM
.016	.41
.030	.76
.125	3.18
.313	7.95
.344	8.74
1.500	38.10

CIRCUIT DIAGRAM AND MARKINGFREQUENCY RANGE 200 Hz TO 20 kHz
POWER LEVEL: .1 W MAXALTITUDE 150,000 FT
WORKING VOLTAGE - 50V
SCHEMATIC

Ⓐ CANCELED AFTER 14 AUGUST 1979
NO SUPERSEDING STANDARD

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. The number of terminals shall be as shown in schematic.
4. Referenced document shall be of the issue in effect on date of invitation for bids.
5. This standard takes precedence over document referenced herein.
6. For vibration and shock test the specimen shall be rigidly mounted on a printed circuit board.
7. The elevated temperature for thermal shock (step 3, method 107C, MIL-STD-202) shall be the maximum operating temperature for the class.

Ⓐ DENOTES CHANGES

P.A. Air Force-85	INTERNATIONAL INTEREST	TITLE TRANSFORMER, AUDIO FREQUENCY, SUB-MINIATURE, TYPE TF5RX21ZZ	MILITARY STANDARD
Other Cust			MS 21419 (USAF)
Procurement Specifications MIL-T-27	SUPERSEDES:		SHEET 1 OF 1

DD FORM 672 (LIMITED COORDINATION)
1 MAY 73

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5950 - F188 - 20

APPROVED 3 MAY 1974 REVISED 14 AUG 79

This military standard has been approved by the Directorate of Electronic Support (AFALD/PTS), Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.