



SECTION B-B

SECTION C-C

SECTION D-D

NS PART NO.	FILE
MS22020-1	

LINKS SHALL BE PROOF LOADED AS SPECIFIED HEREON, INDICATED BY ARROWS.

MATERIAL: STEEL, SPEC MIL-S-5626 OR MIL-S-6049.

METHOD OF FORMING: HOT FORGE.

HEAT TREATMENT: SPEC MIL-H-6873
ROCKWELL C38 TO C42. DECARBURIZATION SHALL NOT EXCEED .010

FINISH: CADMIUM PLATE, SPEC QQ-P-416, TYPE 1, CLASS A.

REMOVE ALL BURS AND SHARP EDGES.

LINKS SHALL BE SMOOTH AND FREE FROM FINS AND PITS.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS : .030

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREON.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

THIS DRAWING HAS BEEN PROMULGATED BY THE DEPARTMENT OF DEFENSE AS THE MILITARY STANDARD TO LIMIT THE SELECTION OF THE ITEM, PRODUCT, OR DESIGN COVERED HEREIN IN ENGINEERING, DESIGN, AND PROCUREMENT. THIS STANDARD SHALL BECOME EFFECTIVE NOT LATER THAN 90 DAYS AFTER THE LATEST DATE OF APPROVAL SHOWN.

(B) REVISED AND REDRAWN

P.A. NAVY - AS Other Cost	TITLE LINK, PARACHUTE BARRAGE TRIANGLE	MILITARY STANDARD	
		MS22020 (AS)	
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES:	SHEET	OF
		1	1

This military standard is approved by NAVAL AIR SYSTEMS COMMAND, Department of the Navy and shall be used by that activity. All other military agencies are required to employ this standard where suitable.

APPROVED 23 MAY 1957 REVISED (B) 27 NOV 81