



DASH NO	HOSE OD		H MAX HT	T THICKNESS	L TOOTH LENGTH	NUMBER OF TEETH
	MIN	MAX				
-1	.469	.500	.093	.017	1.000	8
-2	.563	.625				
-3	.668	.750				
-4	.813	.875		.020		
-5	.938	1.250		.022		

ⓑ MATERIAL: STEEL, CARBON, ANSI/ASTM A682M-77 SHEET AND STRIP, UNTEMPERED.
 FINISH: PHOSPHATE COATING IN ACCORDANCE WITH TT-C-490, TYPE I, FOLLOWED BY ZINC CHROMATE COATING IN ACCORDANCE WITH TT-P-1757, COLOR T.
 THE THIRD PAIR OF TEETH SHALL BE THE MINIMUM ENGAGEMENT FOR USE OF THE CLAMP.
 DIMENSIONS IN INCHES, UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.010

User activities:
 Review activities:
 This Military Standard is approved by the Department and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 2 APR 1963 REVISED A 15 SEP 1972 ⓑ 12 January 1984

P.A. AIR FORCE ⓑ	TITLE ⓑ	MILITARY STANDARD
ARMY - AV NAVY - AS	CLAMP - HOSE	MS 22064
PROCLAMATION SPECIFICATION HOSE	SUPERSEDES:	SHEET 1 OF 1