


User activities: Army ME, AM, WC
 Navy MC, OS
 Air Force
 Reviewer activities: Army MI, MU, AT
 Navy AS, SH
 Air Force 11

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED SUP CLASS
5935



INCHES	MM
.005	.13
.070	1.78
.081	2.06
.095	2.41
.125	3.18
.133	3.38
.140	3.56
.153	3.89
.181	4.60
.190	4.83
.205	5.21
.219	5.56
.240	6.10
.252	6.40
.272	6.91
.350	8.89
.380	9.65
.408	10.31
.465	11.81
.781	19.84
.850	21.59

MS Part No. MS24010-1

DESIGN STANDARD FOR USE WITH MIL-C-28748/5.

NOTES

1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .015 (38 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. Tolerance between any two adjacent contact centers shall be ± .004 (10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ± .006 (15 mm).
5. Contact identification may be located on either side of the contact hole but shall appear on the front and rear of each insert.
6. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
7. Referenced documents shall be of the issue in effect on date of invitation for bid.
8. Complete connectors covered by issues of MS 24010 dated prior to 20 May 1970 are replaced by M28748/5-C00G1A.

(F) denotes changes

APPROVED 12 Aug 1954 REVISED (E) 20 May 1970 (E) 23 June 1972

P A Navy - EC Other Cust AF-80 Army - EL	International Interest	TITLE CONNECTOR, RECTANGULAR, ELECTRICAL, RACK AND PANEL, 14, SIZE 20 SOLDER PIN CONTACTS	MILITARY STANDARD MS24010
Procurement Specification MIL-C-28748		SUPERSEDES	PAGE 1 OF 1

DD FORM 1 Sep 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5935-1822-82