

Review activities:
Navy - AS
USAF - 85

This military standard is approved by the Department of the Air Force and the Naval Air Systems Command and is mandatory for use by these activities. All other military activities are required to employ this standard where suitable.

FED. SUP CLASS																																																																																																																																																				
5945																																																																																																																																																				
<p>STUD, THD 1/4-28 NF-2A NUT, AN341-416 WASHER, AN935B6 WASHER, AN961-416 6 EACH REQUIRED</p> <p>STUD, THD 6-32 NC-2A NUT, AN341-6 WASHER, AN935B6 WASHER, AN961-6 2 EACH REQUIRED</p> <p>TERMINAL COVER</p> <p>NAMEPLATE HERE</p> <p>STUD, THD 6-32 NC-2A NUT, AN341-6 WASHER, AN935B6 WASHER, AN961-6 6 EACH REQUIRED</p>																																																																																																																																																				
<p>CIRCUIT</p> <p>D1, A1</p> <p>A1 — A2</p> <p>B1 — B2</p> <p>C1 — C2</p> <p>X1 — X2</p> <p>D2, A2</p> <p>A1 — A2</p> <p>B1 — B2</p> <p>C1 — C2</p> <p>X1 — X2</p> <p>AUXILIARY CONTACTS</p>																																																																																																																																																				
<table border="1"> <thead> <tr> <th>DASH NO.</th> <th>FIN</th> <th>MAX WEIGHT LBS</th> </tr> </thead> <tbody> <tr> <td>-D1</td> <td></td> <td>2.65</td> </tr> <tr> <td>-D2</td> <td></td> <td>2.80</td> </tr> <tr> <td>-A1</td> <td></td> <td>2.70</td> </tr> <tr> <td>-A2</td> <td></td> <td>2.85</td> </tr> </tbody> </table> <p>DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm .031$.</p> <p>TERMINAL COVERS AND BARRIERS REQUIRED AT TERMINALS. THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</p>		DASH NO.	FIN	MAX WEIGHT LBS	-D1		2.65	-D2		2.80	-A1		2.70	-A2		2.85																																																																																																																																				
DASH NO.	FIN	MAX WEIGHT LBS																																																																																																																																																		
-D1		2.65																																																																																																																																																		
-D2		2.80																																																																																																																																																		
-A1		2.70																																																																																																																																																		
-A2		2.85																																																																																																																																																		
<p>COIL</p> <table border="1"> <thead> <tr> <th></th> <th>NOMINAL</th> <th>MAXIMUM</th> <th>PICK-UP</th> <th>DROP-OUT</th> </tr> </thead> <tbody> <tr> <td>DC VOLTAGE</td> <td>28</td> <td>29</td> <td>18</td> <td>7 + 0, -5.5</td> </tr> <tr> <td>DC CURRENT</td> <td></td> <td>.70</td> <td></td> <td></td> </tr> <tr> <td>AC VOLTAGE</td> <td>115</td> <td>124</td> <td>90</td> <td>30 + 0, -25</td> </tr> <tr> <td>AC CURRENT</td> <td></td> <td>.20</td> <td></td> <td></td> </tr> </tbody> </table> <p>(A) MIN OPERATING CYCLES 50,000 (B) MAX OPERATING TIME .030 SEC (C) MAX RELEASE TIME (AC) .06 SEC (D) MAX RELEASE TIME (DC) .015 SEC (E) MAX DURATION OF CONTACT OPENING DURING SHOCK TEST .002 SEC (F) MAX DURATION CONTACT BOUNCE .002 SEC (K) RUPTURE 8 TIMES RATED ON 115 VOLTS 400 CYCLES & 115/200 VOLTS 400 CYCLES</p>			NOMINAL	MAXIMUM	PICK-UP	DROP-OUT	DC VOLTAGE	28	29	18	7 + 0, -5.5	DC CURRENT		.70			AC VOLTAGE	115	124	90	30 + 0, -25	AC CURRENT		.20																																																																																																																												
	NOMINAL	MAXIMUM	PICK-UP	DROP-OUT																																																																																																																																																
DC VOLTAGE	28	29	18	7 + 0, -5.5																																																																																																																																																
DC CURRENT		.70																																																																																																																																																		
AC VOLTAGE	115	124	90	30 + 0, -25																																																																																																																																																
AC CURRENT		.20																																																																																																																																																		
<p>TYPE OF LOAD</p> <table border="1"> <thead> <tr> <th></th> <th colspan="5">28 VOLTS DC</th> <th colspan="5">115 VOLTS 400 CYCLES AC</th> <th colspan="5">115/200 VOLTS 400 CYCLES AC</th> <th colspan="5">28 VOLTS DC OR 115 VOLTS AC AUXILIARY CONTACTS</th> </tr> <tr> <th></th> <th>A5</th> <th>A8</th> <th>B8</th> <th>C8</th> <th>D10</th> <th>A5</th> <th>A8</th> <th>B8</th> <th>C8</th> <th>D10</th> <th>A5</th> <th>A8</th> <th>B8</th> <th>C8</th> <th>D10</th> <th>A5</th> <th>A8</th> <th>B8</th> <th>C8</th> <th>D10</th> </tr> </thead> <tbody> <tr> <td>RESISTIVE</td> <td>100</td> <td>100</td> <td>100</td> <td></td> <td></td> <td>100</td> <td>100</td> <td>100</td> <td></td> <td></td> <td>100</td> <td>100</td> <td>100</td> <td></td> <td></td> <td>5</td> <td>5</td> <td>5</td> <td></td> <td></td> </tr> <tr> <td>INDUCTIVE</td> <td>100</td> <td>100</td> <td>100</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>5</td> <td>5</td> <td>5</td> <td></td> <td></td> </tr> <tr> <td>MOTOR</td> <td>100</td> <td>100</td> <td>100</td> <td></td> <td></td> <td>75</td> <td>75</td> <td>75</td> <td></td> <td></td> <td>75</td> <td>75</td> <td>75</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>LAMP</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1</td> <td>1</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>MINIMUM</td> <td>10</td> <td>10</td> <td>10</td> <td></td> <td></td> <td>10</td> <td>10</td> <td>10</td> <td></td> <td></td> <td>10</td> <td>10</td> <td>10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>SEE SPECIFICATION</p>			28 VOLTS DC					115 VOLTS 400 CYCLES AC					115/200 VOLTS 400 CYCLES AC					28 VOLTS DC OR 115 VOLTS AC AUXILIARY CONTACTS						A5	A8	B8	C8	D10	A5	A8	B8	C8	D10	A5	A8	B8	C8	D10	A5	A8	B8	C8	D10	RESISTIVE	100	100	100			100	100	100			100	100	100			5	5	5			INDUCTIVE	100	100	100													5	5	5			MOTOR	100	100	100			75	75	75			75	75	75								LAMP																1	1	1			MINIMUM	10	10	10			10	10	10			10	10	10							
	28 VOLTS DC					115 VOLTS 400 CYCLES AC					115/200 VOLTS 400 CYCLES AC					28 VOLTS DC OR 115 VOLTS AC AUXILIARY CONTACTS																																																																																																																																				
	A5	A8	B8	C8	D10	A5	A8	B8	C8	D10	A5	A8	B8	C8	D10	A5	A8	B8	C8	D10																																																																																																																																
RESISTIVE	100	100	100			100	100	100			100	100	100			5	5	5																																																																																																																																		
INDUCTIVE	100	100	100													5	5	5																																																																																																																																		
MOTOR	100	100	100			75	75	75			75	75	75																																																																																																																																							
LAMP																1	1	1																																																																																																																																		
MINIMUM	10	10	10			10	10	10			10	10	10																																																																																																																																							
<p>P.A. Navy - AS Other Cost USAF - 85</p> <p>TITLE RELAY, 100 AMP, 3PST NORMALLY OPEN, CLASS B8, SEALED</p> <p>MILITARY STANDARD MS24195(ASG)</p> <p>PROCUREMENT SPECIFICATION MIL-R-6106</p> <p>SUPERSEDES:</p> <p>SHEET 1 OF 1</p>																																																																																																																																																				

DD FORM 672-1 (limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

U. S. GOVERNMENT PRINTING OFFICE: 1968-241-517/A-1782

REVISED 21 Jan 69
30 Jul 59
APPROVED