


THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL - C - 25427



DASH NO.	TUBE OD INCH	THREAD T MIL-5-8879	A DIA	B DIA	C	D	E		F	G	H	J	J ₁	K	
			±.015	MAX			±.010	±.010		MIN		±.016 -.000	±.032 -.062	J ₁ MAX	DIA MAX
-4	.250	.8750-14 UNJF-3A	.750	1.000	.594	.030	1.125	+ .003	Ⓡ	.355	.250	1.384	3.175	3.769	1.625
-6	.375	1.0625-12 UNJ-3A	.875	1.250			1.375	- .004				1.910	3.566	4.222	1.312
-8	.500	1.3125-12 UNJ-3A	1.063	1.500	.718	.062	1.625	+ .016	.438	.312	1.848	3.990	4.659	1.937	
-10	.625		1.125	1.594	.781		1.938				4.640	5.515	2.125		
-12	.750	1.6250-12 UNJ-3A	1.438	1.750	.906	.093	1.875	+ .020	.500	2.200	4.919	5.753	2.375		
-16	1.000	1.8750-12 UNJ-3A	1.687	2.000	.938	.125	2.125			2.503	5.827	6.847	2.625		
-20	1.250	2.5000-12 UNJ-3A	2.000	2.375	.984		2.750			2.900	6.727	7.897	2.875		

Ⓡ DENOTES CHANGE

INCH-POUND

PREPARING ACTIVITY: NAVY - AS

CUSTODIANS: ARMY - AV NAVY - AS

AIR FORCE - 99 DLA -
REVIEW: ARMY - AR, ME, USAF - 82, DLA - CS,
NADEP - CHERRY POINT

USER: MARINE - MC, ARMY - AT, AF - 71
PROJECT NUMBER: 4730-1002

MILITARY SPECIFICATION SHEET

TITLE
COUPLING ASSEMBLY, HYDRAULIC,
SELF-SEALING, QUICK DISCONNECT,
FLARED FITTING TO INTERNAL THREAD BOSS

SPECIFICATION SHEET NUMBER REV F
MS24333 3 JUL 92

SUPERSEDING REV E
MS24333 28 OCT 87

AMSC - N/A FSC 4730

DISTRIBUTION STATEMENT

A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-C-25427


FORM APPROVED
OMB NO. 0704-0188

F REQUIREMENTS:

MATERIAL: }
FINISH: } SEE PROCUREMENT SPECIFICATION.
PRESSURE RATING: } MIL-C-25427

F NOTES:

1. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.
2. EXAMPLE OF PART NO:



3. THE ASSEMBLY DOES NOT INCLUDE FLANGE STANDARD MS24335.
4. NOTE (a) ON THE DRAWING INDICATES COMPLETE SEPERATION OF COUPLING HALVES, ALLOWING LATERAL DISPLACEMENT WITHOUT INTERFERENCE BETWEEN COUPLING HALVES.
5. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
6. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

PREPARING ACTIVITY: NAVY - AS
 CUSTODIANS: ARMY - AV NAVY - AS
 AIR FORCE - 99 DLA -
 REVIEW: USAF - 82, DLA - CS, ARMY - AR, ME
 USER: MARINE CORPS - MC, ARMY - AT, AF - 71
 PROJECT NUMBER: 4730-0147

MILITARY SPECIFICATION SHEET
 TITLE
 COUPLING ASSEMBLY, HYDRAULIC,
 SELF-SEALING, QUICK DISCONNECT,
 FLARED FITTING TO INTERNAL THREAD BOSS

SPECIFICATION SHEET NUMBER REV F
MS24333 3 JUL 92
 SUPERSEDING REV E
MS24333 28 OCT 87
 AMSC - N/A FSC 4730

DISTRIBUTION STATEMENT
 A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

PAGE 2 OF 2