


FORM APPROVED
OMB NO. 0704-0188

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL - C - 25427



DASH NO.	TUBE OD INCH	THREAD T SPECIFICATION MIL-S-8879	A +.015 DIA	B MAX DIA	C ±.010	D ±.010	E		F MIN	G +.016 - .000	H MAX	J +.032 - .062	J 1 MAX	K DIA MAX
-4	.250	.8750-14 UNJF-3A	.750	1.000	.594	.030	1.125	+.003	E	.250	1.384	3.078	3.672	1.625
-6	.375	1.0625-12 UNJ-3A	.875	1.250			1.375	-.004						
-8	.500	1.3125-12 UNJ-3A	1.063	1.500	.906	.062	1.625	±.016	.438	.312	1.848	3.893	4.562	1.937
-10	.625		1.125	1.594			1.938							
-12	.750	1.6250-12 UNJ-3A	1.438	1.750	.984	.125	1.875	±.020	.500	.312	2.200	4.812	5.656	2.375
-16	1.000	1.8750-12 UNJ-3A	1.687	2.000			.938							
-20	1.250	2.5000-12 UNJ-3A	2.000	2.375			2.750				2.900	5.739	7.800	2.875

E

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

INCH-POUND

E DENOTES CHANGE

PREPARING ACTIVITY: NAVY - AS CUSTODIANS: ARMY - AV NAVY - AS AIR FORCE - 99 DLA - REVIEW: USAF - 82, ARMY - AR USER: PROJECT NUMBER: 4730-1003	MILITARY SPECIFICATION SHEET TITLE COUPLING ASSEMBLY, HYDRAULIC, SELF-SEALING, FLARELESS FITTING TO INTERNAL THREAD BOSS	SPECIFICATION SHEET NUMBER REV E MS24334 3 JUL 92
		SUPERSADDING REV D MS24334 30 OCT 87
		AMSC - N/A FSC 4730
DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.		PAGE 1 OF 2

FORM APPROVED
OMB NO. 0704-0188


THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL - C - 25427

(E) REQUIREMENTS:

MATERIAL:
FINISH:
PRESSURE RATING: } SEE PROCUREMENT SPECIFICATION.
MIL-C-25427

(E) NOTES:

- UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.
- EXAMPLE OF PART NO:



- THE ASSEMBLY DOES NOT INCLUDE FLANGE STANDARD MS24335.
- NOTE (a) ON THE DRAWING INDICATES COMPLETE SEPERATION OF COUPLING HALVES, ALLOWING LATERAL DISPLACEMENT WITHOUT INTERFERENCE BETWEEN COUPLING HALVES.
- IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
- REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

PREPARING ACTIVITY: NAVY - AS CUSTODIANS: ARMY - AV NAVY - AS AIR FORCE - 99 DLA - REVIEW: USAF - 82, ARMY - AR, ME, DLA - CS USER: MARINE CORPS - MC, ARMY - AT, AF - 71 PROJECT NUMBER: 4730-1003	MILITARY SPECIFICATION SHEET TITLE COUPLING ASSEMBLY, HYDRAULIC, SELF-SEALING, FLARELESS FITTING TO INTERNAL THREAD BOSS	SPECIFICATION SHEET NUMBER REV E MS24334 3 JUL 92
		SUPERSEDING REV D MS24334 30 OCT 87
DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.		AMSC - N/A FSC 4730 PAGE 2 OF 2