



FED. SUP CLASS.
4730

Review activities:
Navy - AS
USAF - R2, 11



SECTION I-I

This military standard is approved by the Department of the Air Force and the Naval Air Systems Command and is mandatory for use by these activities. All other military activities are required to employ this standard where suitable.

DASH NO.	EQUIV TUBE DIA	A +.000 -.010	B +.000 -.020	C ±.010	D ±.010	E +.010 -.000	F +.000 -.010	G +.000 -.016	H ±.015	WT IN LB
4	1/4	2.250	1.625	1.516	.876	1.130	1.090			
6	3/8	2.500	1.812	1.732	1.000	1.380	1.340	.250		
8	1/2	2.750	1.938	1.948	1.126	1.642	1.602			
10	5/8		2.125						.060	
12	3/4	3.000	2.375	2.162	1.250	1.892	1.852	.312		
16	1	3.250	2.625	2.380	1.376	2.146	2.106			
20 (B)	1-1/4	4.125	3.250	2.938	1.750	2.772	2.482			

MATERIAL: SEE PROCUREMENT SPECIFICATION.

FINISH: SEE PROCUREMENT SPECIFICATION.

DIMENSIONS IN INCHES.

FLANGE FOR USE WITH STANDARDS MS24333 AND MS24334.

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

CUSTODIANS PA USAF-82 Oast Navy-AS (B)	OTHER INT. A - N - AF -	MILITARY STANDARD	MS24335 (ASG)
		FLANGE, BULKHEAD MOUNTING, HYDRAULIC, SELF-SEALING COUPLING	
Procurement Specification MIL-C-25427	SUPERSEDES:	SHEET 1 OF 1	