

NOTICE OF CANCELLATION

INCH-POUND

MS24394G
 NOTICE 1
 22 April 1999

MILITARY STANDARD

ELBOW, TUBE, BULKHEAD, 90°, PRECISION TYPE

MS24394G, dated 16 November 1984, is hereby cancelled. Future acquisitions for this item should refer to Society of Automotive Engineers (SAE) Aerospace Standard (AS) AS1038, "Elbow, 90°, Standard and Reducer, Bulkhead, Flared Tube."

Table 1 provides a detailed cross-reference of cancelled MS24394 Part or Identifying Numbers (PINs) and replacement AS1038 PINs. The use of "AS" parts is preferable, but "MS" parts may be used for a period of three years from the date of this notice to deplete existing stock. Users are cautioned to evaluate replacements for their particular application.

(DoD activities may obtain copies of SAE AS1038 from the DoDSSP, Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other Government agencies may purchase copies from the Society of Automotive Engineers International, 400 Commonwealth Drive, Warrendale, PA 15096-0001.)

Custodians:

Army - AV
 Navy - AS
 Air Force - 99
 DLA - CC

Preparing activity:

DLA - CC

(Project 4730-0425)

Review activities:

Army - AT
 Air Force - 82

MS24394G
NOTICE 1

TABLE 1 - Cross-Reference Data

Cancelled AN PIN	Tube Size	Replacement AS PIN	Cancelled AN PIN	Tube Size	Replacement AS PIN
MS24394-2	.125	AS1038-0202	MS24394-8	.500	AS1038-0808
MS24394D2	.125	AS1038D0202	MS24394D8	.500	AS1038D0808
MS24394J2	.125	AS1038J0202	MS24394J8	.500	AS1038J0808
MS24394K2	.125	AS1038K0202	MS24394K8	.500	AS1038K0808
MS24394S2	.125	AS1038S0202	MS24394S8	.500	AS1038S0808
MS24394T2	.125	AS1038T0202	MS24394T8	.500	AS1038T0808
MS24394W2	.125	AS1038W0202	MS24394W8	.500	AS1038W0808
MS24394-3	.188	AS1038-0303	MS24394-10	.625	AS1038-1010
MS24394D3	.188	AS1038D0303	MS24394D10	.625	AS1038D1010
MS24394J3	.188	AS1038J0303	MS24394J10	.625	AS1038J1010
MS24394K3	.188	AS1038K0303	MS24394K10	.625	AS1038K1010
MS24394S3	.188	AS1038S0303	MS24394S10	.625	AS1038S1010
MS24394T3	.188	AS1038T0303	MS24394T10	.625	AS1038T1010
MS24394W3	.188	AS1038W0303	MS24394W10	.625	AS1038W1010
MS24394-4	.250	AS1038-0404	MS24394-12	.750	AS1038-1212
MS24394D4	.250	AS1038D0404	MS24394D12	.750	AS1038D1212
MS24394J4	.250	AS1038J0404	MS24394J12	.750	AS1038J1212
MS24394K4	.250	AS1038K0404	MS24394K12	.750	AS1038K1212
MS24394S4	.250	AS1038S0404	MS24394S12	.750	AS1038S1212
MS24394T4	.250	AS1038T0404	MS24394T12	.750	AS1038T1212
MS24394W4	.250	AS1038W0404	MS24394W12	.750	AS1038W1212
MS24394-5	.312	AS1038-0505	MS24394-16	1.000	AS1038-1616
MS24394D5	.312	AS1038D0505	MS24394D16	1.000	AS1038D1616
MS24394J5	.312	AS1038J0505	MS24394J16	1.000	AS1038J1616
MS24394K5	.312	AS1038K0505	MS24394K16	1.000	AS1038K1616
MS24394S5	.312	AS1038S0505	MS24394S16	1.000	AS1038S1616
MS24394T5	.312	AS1038T0505	MS24394T16	1.000	AS1038T1616
MS24394W5	.312	AS1038W0505	MS24394W16	1.000	AS1038W1616
MS24394-6	.375	AS1038-0606	MS24394-20	1.250	AS1038-2020
MS24394D6	.375	AS1038D0606	MS24394D20	1.250	AS1038D2020
MS24394J6	.375	AS1038J0606	MS24394J20	1.250	AS1038J2020
MS24394K6	.375	AS1038K0606	MS24394K20	1.250	AS1038K2020
MS24394S6	.375	AS1038S0606	MS24394S20	1.250	AS1038S2020
MS24394T6	.375	AS1038T0606	MS24394T20	1.250	AS1038T2020
MS24394W6	.375	AS1038W0606	MS24394W20	1.250	AS1038W2020

MS24394G
NOTICE 1

TABLE 1 - Cross-Reference Data (Continued)

Cancelled AN PIN	Tube Size	Replacement AS PIN	Cancelled AN PIN	Tube Size	Replacement AS PIN
MS24394-24	1.500	AS1038-2424	MS24394-32	2.000	AS1038-3232
MS24394D24	1.500	AS1038D2424	MS24394D32	2.000	AS1038D3232
MS24394J24	1.500	AS1038J2424	MS24394J32	2.000	AS1038J3232
MS24394K24	1.500	AS1038K2424	MS24394K32	2.000	AS1038K3232
MS24394S24	1.500	AS1038S2424	MS24394S32	2.000	AS1038S3232
MS24394T24	1.500	AS1038T2424	MS24394T32	2.000	AS1038T3232
MS24394W24	1.500	AS1038W2424	MS24394W32	2.000	AS1038W3232
MS24394-28	1.750	Not available			
MS24394D28	1.750	Not available			
MS24394J28	1.750	Not available			
MS24394K28	1.750	Not available			
MS24394S28	1.750	Not available			
MS24394T28	1.750	Not available			
MS24394W28	1.750	Not available			