


NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government hereby incurs no responsibility, nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights, or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the United States Department of the Navy and the Department of the Air Force and is intended for use by that activity. All other military activities are required to employ this standard where suitable.

FED. SUP CLASS
6210



DASH NO.	COLOR
-1	RED
-2	GREEN
-3	BLUE
-4	YELLOW

MATERIAL TO BE CLASS B IN ACCORDANCE WITH MIL-C-7989 EXCEPT TEMPERED TO WITHSTAND THE FOLLOWING TEMPERATURE SHOCK TEST: SAMPLES SHALL BE HEATED IN AN OVEN AT $150 \pm 2^\circ\text{C}$ FOR 1 HOUR AND THEN IMMEDIATELY IMMERSED FOR 1 MINUTE IN WATER AT 0° TO 5°C .

COLORS TO BE TYPE I, GRADE A, IN ACCORDANCE WITH MIL-C-25050 FOR RED, GREEN, AND YELLOW FILTERS AND TYPE I, GRADE B, IN ACCORDANCE WITH MIL-C-25050 FOR BLUE FILTERS.

DIMENSIONS IN INCHES, UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm.016$.

NO DRAWING NUMBER AND MANUFACTURERS IDENTIFICATION TO BE MARKED ON BOTTOM OF FLANGE.

(E) THIS STANDARD CONVERTED FROM MS24502(USAF) TO MS24502(ASG).

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

P.A. USAF Other Cust Navy - Weps	TITLE FILTER, MARKER LIGHT, AIRPORT RUNWAY, GLASS	MILITARY STANDARD
		MS24502(ASG)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:	SHEET 1 OF 1