

MS25068K

NOTES:

1. All dimensions are in inches.
2. For hardware and terminal screw detail specifications see supplement of MIL-DTL-83731.
3. Unless otherwise specified, tolerance is $\pm .020$ on two place decimals and $\pm .005$ on three place decimals.
4. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

FIGURE1. Dimensions and configuration Continued.

REQUIREMENTS:

All switches on this standard are designed so that the movement of the switch mechanism is opposite to that of the toggle lever.

Maximum weight is 0.16 lbs.

Electrical Endurance: 10,000 Cycles.
Mechanical Endurance: 20,000 Cycles.

Electrical rating: See table I.

Referenced documents shall be of the issue in effect on the date of invitation for bid.

Table I Detail Requirements.

MS part No.	Former Ms Part No.	Circuit with Toggle Lever In			Current Capacity (Amperes Per Pole)					
					Direct current			Alternating current (400 Hertz)		
		Keying side	Center	Opposite keying side	Lamp-Load Circuit	Resistiv e Circuit	Inductive Circuit	Lamp load Circuit	Resistive Circuit	Inductive Circuit
					28 Volts	28 volts	28 Volts	115 volts	115 Volts	115 Volts
MS25068-21	MS25068-1	On	Off	On	5	20	12	4	20	15
MS25068-23	MS25068-3		None							
MS25068-24	MS25068-11	None	Off		4	18	10	2	11	5
MS25068-25	MS25068-13		Mom Off							
MS25068-26	MS25068-10	Mom-On	None	On						
MS25068-27	MS25068-7		Mom-On							
MS25068-28	MS25068-12		None							
MS25068-31	MS25068-5		On							

MS25068K

Referenced documents
MIL-DTL-83731

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – CR
Navy – AS
Air Force – 11
DLA – CC

Preparing activity:
DLA – CC
Project (5930-2005-004)

Review activities:
Army – AV
Navy – EC
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://assist.daps.dla.mil/>.