

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government hereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have furnished, furnished, or may supply the said drawings, specifications, or other data is not to be regarded by implication or otherwise as an endorsement, licensing the holder or any other person as to the propriety or conveying any right or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Department of the Navy, under the authority of the Department of the Navy, and is mandatory for use by that activity. All other military activities are required to employ this standard when suitable.

		FED. SUP CLASS. 1680
<p>(a) DIMENSION A IS A MULTIPLE OF .375 (WITH MINIMUM OF 1.125 AND A MAXIMUM OF 9). TOLERANCE $\pm .000$ $\pm .030$.</p> <p>(b) DIMENSION B IS 1.125 LESS THAN A (THREE MULTIPLES OF .375). DISTANCE BETWEEN STUDS SHALL NOT EXCEED 4.875. TOLERANCE IS $\pm .005$.</p> <p>(c) SPACE AVAILABLE FOR MOUNTING OF COMPONENT CONTROLS, DISCONNECT RECEPTACLE WITH MOUNTING BRACKET AND MATING DISCONNECT PLUG AND CABLE CLAMP. WHEN A DUST COVER IS USED, IT SHALL BE CONTAINED WITHIN THIS AREA.</p> <p>(d) MAXIMUM AVAILABLE SPACE FOR THE EXIT OF CABLES, ETC. FROM THE CONTROL PANEL. DRESSED CABLES MUST LIE WITHIN THIS AREA AND RUN IN THE DIRECTION OF THE CONTROL PANEL LENGTH. DIMENSIONS IN INCHES. FOR INSTALLATION SEE MS25213.</p>		
<p>FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</p> <p>THIS IS A DESIGN STANDARD. NOT TO BE USED AS A PART NUMBER.</p>		
P.A. USAF Other Cust Navy-Wep	TITLE CONTROL PANEL, CONSOLE TYPE, AIRCRAFT EQUIPMENT, BASIC DIMENSIONS	MILITARY STANDARD MS25212(ASG)
PROCUREMENT SPECIFICATION MIL-C-6781	SUPERSEDES: AND10479	SHEET 1 OF 1