

INCH-POUND

MS25225J

22 February 2007

SUPERSEDING

MS25225H


21 December 2005

DETAIL SPECIFICATION SHEET


GUARD, SWITCH, 3 POSITION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-DTL-7703.

FIGURE 1. Dimensions and configuration -1.

MS25225J

FIGURE 2. Dimensions and configuration -2.

MS25225J

TABLE I. Detail requirements.

Dash No.	Type	Panel Thickness (REF)	Operating Force	Remarks
-1	1-Hole Mounting	.050 to .248	1.0 to 2.5 LB	
-2 <u>1/</u>	3-Hole Mounting	.050 to .081		Identical to -1, Except Keyway is Rotated 180°
-3	1-Hole Mounting	.050 to .248		

Notes:

Material: Plastic molded red, color STD 11136, FED-STD-595.

Finish: Corrosion resistant, zinc plate ASTM B633, black enamel, lusterless, color 37038 or semigloss, color 27038, FED-STD-595 or equivalent.

Guard shall remain in either open or closed position.

Opening the guard shall not change the position of the switch contacts.

When lever is in upward position, closing guard shall throw lever to center position.

When lever is in downward position, closing guard shall not throw lever to center position.

Referenced Documents

MIL-DTL-7703

ASTM-B633

FED-STD-595

The margins of this specification are marked with vertical lines to indicate where modifications made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:

Army - CR

Navy - AS

Air Force - 11

DLA - CC

Preparing activity:

DLA - CC

(Project 5930-2007-041)

Review activities:

Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://assist.daps.dla.mil/>.