

USER SYMBOLS:

REVIEWER SYMBOLS:

ARMY - ME
NAVY -
USAF -

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DDSSS."

This military standard is approved for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

							FED. SUP CLASS 6240																																																																						
<table border="1"> <thead> <tr> <th>inch</th> <th>mm</th> </tr> </thead> <tbody> <tr><td>.025</td><td>0.64</td></tr> <tr><td>.074</td><td>1.88</td></tr> <tr><td>.080</td><td>2.03</td></tr> <tr><td>.249</td><td>6.32</td></tr> <tr><td>.316</td><td>8.03</td></tr> <tr><td>.492</td><td>12.50</td></tr> <tr><td>.508</td><td>12.90</td></tr> <tr><td>.5925</td><td>15.05</td></tr> <tr><td>.6025</td><td>15.30</td></tr> <tr><td>1.250</td><td>31.75</td></tr> <tr><td>1.420</td><td>36.07</td></tr> <tr><td>1.600</td><td>38.10</td></tr> <tr><td>2.375</td><td>60.33</td></tr> </tbody> </table>									inch	mm	.025	0.64	.074	1.88	.080	2.03	.249	6.32	.316	8.03	.492	12.50	.508	12.90	.5925	15.05	.6025	15.30	1.250	31.75	1.420	36.07	1.600	38.10	2.375	60.33																																									
inch	mm																																																																												
.025	0.64																																																																												
.074	1.88																																																																												
.080	2.03																																																																												
.249	6.32																																																																												
.316	8.03																																																																												
.492	12.50																																																																												
.508	12.90																																																																												
.5925	15.05																																																																												
.6025	15.30																																																																												
1.250	31.75																																																																												
1.420	36.07																																																																												
1.600	38.10																																																																												
2.375	60.33																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">DASH NO.</th> <th rowspan="2">TRADE NO</th> <th rowspan="2">TYPE PER MTL-L-6363</th> <th colspan="2">RATED</th> <th rowspan="2">MAX AMPERES</th> <th rowspan="2">FILAMENT TYPE</th> <th rowspan="2">FINISH</th> <th rowspan="2">AVERAGE LIFE (HOURS)</th> </tr> <tr> <th>VOLTS</th> <th>CANDLE-POWER</th> </tr> </thead> <tbody> <tr> <td>311</td> <td>311</td> <td>I</td> <td rowspan="4">28</td> <td>50</td> <td rowspan="4">1.5</td> <td rowspan="4">C-2V</td> <td>CLEAR - NO COATING</td> <td rowspan="4">300</td> </tr> <tr> <td>SB311</td> <td>311SB</td> <td>I</td> <td>(SEE NOTE 3)</td> </tr> <tr> <td>R311</td> <td>311R</td> <td>I</td> <td></td> </tr> <tr> <td>3011</td> <td>3011</td> <td>I</td> <td>44</td> <td>CLEAR - NO COATING</td> </tr> <tr> <td colspan="9"> <p>REQUIREMENTS:</p> <ol style="list-style-type: none"> LIGHT EMITTED BY RED LAMPS SHALL CONFORM TO MIL-C-25050 FOR INSTRUMENT AND PANEL LIGHTING RED. RED COATINGS, WHEN USED, SHALL BE TRANSLUCENT. FINISH CLEAR, EXCEPT TOP TO RECEIVE AN ALUMINIZED REFLECTIVE COATING. DISTANCE FROM EDGE OF COATING TO TOPS OF BAYONET PINS SHALL BE APPROXIMATELY EQUAL TO LIGHT CENTER LENGTH, 1.250. <p>NOTES:</p> <ol style="list-style-type: none"> DIMENSIONS ARE IN INCHES. METRIC EQUIVALENTS (TO THE NEAREST .01 mm) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 mm. RATED CANDLEPOWER APPLIES TO LAMP BEFORE RED COATING OR REFLECTIVE COATING IS APPLIED. PART NUMBERS MS25235-311, SB311, and R311 REPLACE AND ARE INTERCHANGEABLE WITH AN3133-311, -SB311, and -R311 RESPECTIVELY. CERTAIN PROVISIONS OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ASCC 12/2 AND STANAG 3544. WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED WHICH WILL AFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRIATE RECONCILIATION ACTION THROUGH INTERNATIONAL STANDARDIZATION CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES IF REQUIRED. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. </td> </tr> <tr> <td colspan="3"> <p>P.A. NAVY - AS Other Cust USAF - 99 ARMY - AV</p> </td> <td colspan="3"> <p>INTER-NATIONAL INTEREST (SEE NOTE 5)</p> </td> <td colspan="3"> <p>TITLE LAMP, INCANDESCENT, SINGLE-CONTACT BAYONET CANDELABRA BASE, S-11 BULB</p> </td> </tr> <tr> <td colspan="3"> <p>PROCUREMENT SPECIFICATION MIL-L-6363</p> </td> <td colspan="3"> <p>SUPERSEDES: AN3133, MS0025235 (USAF)</p> </td> <td colspan="3"> <p>MILITARY STANDARD MS25235</p> </td> </tr> <tr> <td colspan="3"></td> <td colspan="3"></td> <td colspan="3"> <p>SHEET 1 OF 1</p> </td> </tr> </tbody> </table>									DASH NO.	TRADE NO	TYPE PER MTL-L-6363	RATED		MAX AMPERES	FILAMENT TYPE	FINISH	AVERAGE LIFE (HOURS)	VOLTS	CANDLE-POWER	311	311	I	28	50	1.5	C-2V	CLEAR - NO COATING	300	SB311	311SB	I	(SEE NOTE 3)	R311	311R	I		3011	3011	I	44	CLEAR - NO COATING	<p>REQUIREMENTS:</p> <ol style="list-style-type: none"> LIGHT EMITTED BY RED LAMPS SHALL CONFORM TO MIL-C-25050 FOR INSTRUMENT AND PANEL LIGHTING RED. RED COATINGS, WHEN USED, SHALL BE TRANSLUCENT. FINISH CLEAR, EXCEPT TOP TO RECEIVE AN ALUMINIZED REFLECTIVE COATING. DISTANCE FROM EDGE OF COATING TO TOPS OF BAYONET PINS SHALL BE APPROXIMATELY EQUAL TO LIGHT CENTER LENGTH, 1.250. <p>NOTES:</p> <ol style="list-style-type: none"> DIMENSIONS ARE IN INCHES. METRIC EQUIVALENTS (TO THE NEAREST .01 mm) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 mm. RATED CANDLEPOWER APPLIES TO LAMP BEFORE RED COATING OR REFLECTIVE COATING IS APPLIED. PART NUMBERS MS25235-311, SB311, and R311 REPLACE AND ARE INTERCHANGEABLE WITH AN3133-311, -SB311, and -R311 RESPECTIVELY. CERTAIN PROVISIONS OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ASCC 12/2 AND STANAG 3544. WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED WHICH WILL AFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRIATE RECONCILIATION ACTION THROUGH INTERNATIONAL STANDARDIZATION CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES IF REQUIRED. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. 									<p>P.A. NAVY - AS Other Cust USAF - 99 ARMY - AV</p>			<p>INTER-NATIONAL INTEREST (SEE NOTE 5)</p>			<p>TITLE LAMP, INCANDESCENT, SINGLE-CONTACT BAYONET CANDELABRA BASE, S-11 BULB</p>			<p>PROCUREMENT SPECIFICATION MIL-L-6363</p>			<p>SUPERSEDES: AN3133, MS0025235 (USAF)</p>			<p>MILITARY STANDARD MS25235</p>									<p>SHEET 1 OF 1</p>		
DASH NO.	TRADE NO	TYPE PER MTL-L-6363	RATED		MAX AMPERES	FILAMENT TYPE	FINISH	AVERAGE LIFE (HOURS)																																																																					
			VOLTS	CANDLE-POWER																																																																									
311	311	I	28	50	1.5	C-2V	CLEAR - NO COATING	300																																																																					
SB311	311SB	I		(SEE NOTE 3)																																																																									
R311	311R	I																																																																											
3011	3011	I		44			CLEAR - NO COATING																																																																						
<p>REQUIREMENTS:</p> <ol style="list-style-type: none"> LIGHT EMITTED BY RED LAMPS SHALL CONFORM TO MIL-C-25050 FOR INSTRUMENT AND PANEL LIGHTING RED. RED COATINGS, WHEN USED, SHALL BE TRANSLUCENT. FINISH CLEAR, EXCEPT TOP TO RECEIVE AN ALUMINIZED REFLECTIVE COATING. DISTANCE FROM EDGE OF COATING TO TOPS OF BAYONET PINS SHALL BE APPROXIMATELY EQUAL TO LIGHT CENTER LENGTH, 1.250. <p>NOTES:</p> <ol style="list-style-type: none"> DIMENSIONS ARE IN INCHES. METRIC EQUIVALENTS (TO THE NEAREST .01 mm) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 mm. RATED CANDLEPOWER APPLIES TO LAMP BEFORE RED COATING OR REFLECTIVE COATING IS APPLIED. PART NUMBERS MS25235-311, SB311, and R311 REPLACE AND ARE INTERCHANGEABLE WITH AN3133-311, -SB311, and -R311 RESPECTIVELY. CERTAIN PROVISIONS OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ASCC 12/2 AND STANAG 3544. WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED WHICH WILL AFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRIATE RECONCILIATION ACTION THROUGH INTERNATIONAL STANDARDIZATION CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES IF REQUIRED. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. 																																																																													
<p>P.A. NAVY - AS Other Cust USAF - 99 ARMY - AV</p>			<p>INTER-NATIONAL INTEREST (SEE NOTE 5)</p>			<p>TITLE LAMP, INCANDESCENT, SINGLE-CONTACT BAYONET CANDELABRA BASE, S-11 BULB</p>																																																																							
<p>PROCUREMENT SPECIFICATION MIL-L-6363</p>			<p>SUPERSEDES: AN3133, MS0025235 (USAF)</p>			<p>MILITARY STANDARD MS25235</p>																																																																							
						<p>SHEET 1 OF 1</p>																																																																							

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

(PROJECT NO. 6240-0367)

PLATE NO. 16320

ENGINEERING SPECIFICATIONS
AND STANDARDS DEPARTMENT DATE
NAVAL AIR ENGINEERING CENTER

APPROVED 5 APR 57 REVISED (A) 7 JUL 72 (B) 12 OCT 73 (C) 12 OCT 83 (D) 23 AUG 1985