

Reviewers:
Navy - AS, EC
Air Force 85, II

NSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

any standard is approved by the Department of Defense and is
by all activities. Selection for all new engineering and design
applications and for repetitive use shall be made from this document.

PROJ 5945-183-2

FEJ. SUP CLASS
5945

TO CLOSE CONTACTS A3, B3, C3, & D3 ENERGIZE TRIP COIL
TO CLOSE CONTACTS A1, B1, C1, & D1 ENERGIZE RESET COIL
CORRECT POLARITY OF COIL LEADS MUST BE OBSERVED

NOTES:

1. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm .010$.
2. THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCE DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.
3. TERMINAL NUMBERS NEED NOT APPEAR ON RELAY HEADER PROVIDED THERE IS AFFIXED TO THE RELAY A SUITABLE LEGIBLE CIRCUIT DIAGRAM THAT IDENTIFIES EACH TERMINAL LOCATION SPECIFIED HEREON.
4. RELAY IS MAGNETICALLY LATCHED IN BOTH POSITIONS. CAUTION NOTE TO OBSERVE POLARITY MUST APPEAR ON RELAYS WITH DC COILS.
5. SHOCK, VIBRATION AND ACCELERATION REQUIREMENT APPLICABLE WITH COILS DE-ENERGIZED.

② DENOTES CHANGES ② CANCELED AFTER 31 JULY 1986 NO SUPERSEDING STANDARD

MS PART NUMBER	TYPE	COIL	TERMINAL TYPE	MOUNTING	MAX WEIGHT IN POUNDS
MS25280-1	I	DC	SOLDER HOOK	BRACKET	0.5

P.A.	TITLE	MILITARY STANDARD
NAVY - AS Other Comd AIR FORCE 85	RELAY, MAGNETIC LATCH, 10 AMP, 4 PDT, TYPE I (HERMETICALLY SEALED) SOLDER TERMINAL, BRACKET MOUNTED	MS 25280
PROCUREMENT SPECIFICATION MIL-R-6106	SUPERSEDES:	SHEET 1 OF 2

