

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

FED. SUP CLASS 5935					
<p>TERMINAL DESIGNATIONS TO APPEAR ON BOTH SIDES OF SOCKET</p> <p>1.000 DIA, .093, .188, .585 MAX, .361</p> <p>LOCATING PIN HOLE</p> <p>PIN RECEPTACLE LAYOUT</p> <p>DETAIL A</p> <table border="1"> <tr> <th>DASH NO.</th> <th>MAX WT LB WITHOUT HARDWARE</th> </tr> <tr> <td>-4</td> <td>.010</td> </tr> </table> <p>(A) INSERTION AND WITHDRAWAL FORCES: MEASURED WITH: .0390 <math>\pm</math>.0001 DIA PIN 1 OZ MIN</p> <p>(B) VIBRATION, MIL-STD-202, METHOD 204, CONDITION B, WITH MS25325 INSERTED 10 G, 10 TO 1500 CPS</p> <p>(C) CONTACT TABS, PARA 3.8, MIL-S-12883 NOT APPLICABLE</p> <p>(D) AMBIENT TEMPERATURE RANGE -65°C TO +120°C</p> <p>(E) PIN ENTRY PARA 3.3.1.2, MIL-C-5015</p> <p>(F) DIELECTRIC, MIN, WITHOUT MATING RELAY ENGAGED 2500 VRMS</p> <p>SEA LEVEL 500 VRMS</p> <p>ALTITUDE (80,000 FT) MS25325</p> <p>(G) MATING RELAY</p> <p>MATERIAL: BODY, MIL-M-19833, TYPE GHI-30F. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS <math>\pm</math>.010.</p> <p>(B) ENTIRE STANDARD REVISED.</p> <p>FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</p> <div> <div> P.A. Navy - Wep Other Cust USAF - SGEE </div> <div> TITLE SOCKET, RELAY, ELECTRICAL, 14 CONTACTS, 5 AMP </div> <div> MILITARY STANDARD MS25326(ASG) SHEET 1 OF 1 </div> </div> <div> PROCUREMENT SPECIFICATION MIL-S-12883 </div> <div> SUPERSEDES: </div>		DASH NO.	MAX WT LB WITHOUT HARDWARE	-4	.010
DASH NO.	MAX WT LB WITHOUT HARDWARE				
-4	.010				
<p>BOTTOM MOUNTED</p> <p>USE WASHERS SUPPLIED WITH MS25332-1 TO ACCOMPLISH THE INDICATED SPACING</p> <p>TOP MOUNTED</p> <p>MOUNTING HOLE LAYOUT</p>					

This standard has been approved by the Dep (Department of the Navy) and the Department of the USAF and is mandatory for use by their activity. All other military activities are required to employ this standard where suitable.