

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government hereby incurs no responsibility, nor any obligation whatsoever, and the fact that the Government may have furnished, furnished, or in any way supplied the said drawing, specification, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any right or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Dept. of the Navy (Department of the Navy) and the Department of the USAF and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

CURRENT CAPACITY 28 VOLTS DC						CURRENT CAPACITY 115 VOLTS, 400 CYCLES AC		
RESISTIVE	INDUCTIVE	MOTOR	RESISTIVE	INDUCTIVE	MOTOR			
15	10	10	15	15	6			

MATERIAL: CASE, COVER AND PUSH BUTTON: DIALYL PHTHALATE.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMAL  $\pm .015$ .

EXACT SHAPE OF SWITCH OPTIONAL, PROVIDED DIMENSIONS SPECIFIED ARE NOT EXCEEDED.

TEST REQUIREMENT: FOR SHORT CIRCUIT TEST, USE SIZE AW-16 CABLE AND CIRCUIT BREAKER MS25017-15.

**⑥ CANCELLED - For procurement use MIL-S-8805/17**

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

P.A. USAF 85 Other Cust USAF 85	TITLE SWITCH, SENSITIVE - MAINTAINED 15 AMP 6 CIRCUIT, SIDE SOLDER TERMINAL	MILITARY STANDARD <b>MS25353(ASG)</b>
PROCUREMENT SPECIFICATION MIL-S-6713	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 59 672-1 (limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. 5930-F230-11