

INCH-POUND

MS25455J
 06 October 2020
 SUPERSEDING
 MS25455H
 27 November 2003

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 5 AMPERES,
 2 PDT, TYPE I, MAGNETIC LATCH, SOCKET MOUNTED,
 HERMETICALLY SEALED

INACTIVE FOR NEW DESIGN AFTER 5 JUN 1987.
 NO SUPERSEDING SPECIFICATION

This specification is approved for use by all Departments
 and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall
 consist of this specification and the latest issue of [MIL-PRF-6106](#).





FIGURE 1. Dimensions and configurations.



MS25455J



NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 0.010 (0.25 mm).
4. Terminal numbers need not appear on relay header provided there is affixed to the relay a suitable legible circuit diagram that permanently and positively identifies each terminal location specified hereon.
5. The use of diodes on ac relays is optional. Actual application must be shown on label.
6. Pins to be perpendicular to header surface within 1 degree.
7. Relay is magnetically latched in both positions. Caution note to observe polarity must appear on relays with dc coils.
8. Shock, vibration, and acceleration requirements applicable with coils de-energized.
9. In the event of conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.
10. Referenced Government documents of the issue listed in that issue of the Acquisition Streamlining and Standardization Information System (ASSIST) specified in the solicitation forms a part of this standard to the extent specified herein.
11. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals shall be gold plated. One system for gold plating that may be used is [ASTM-B488](#), type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.
12. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have thickness .075, recessed .047 in to bracket. Gasket material according to [SAE-AMS3332](#) has been considered acceptable.

	Inches	mm	Inches	mm
	.001	0.03	.165	4.19
	.005	0.13	.203	5.16
	.010	0.25	.253	6.43
	.040	1.02	.304	7.72
	.047	1.19	.330	8.38
	.062	1.57	.344	8.74
	.075	1.91	.456	11.58
	.077	1.96	.608	15.44
	.093	2.36	.700	17.78
	.143	3.63	1.500	38.10
	.147	3.73	1.750	44.45
	.152	3.86	1.844	46.84
			2.187	55.55

FIGURE 1. Dimensions and configurations - Continued.

MS25455J

TABLE I. Dash numbers and characteristics.

Dash number MS25455-	Type	Coil	Terminal type	Max weight in pounds
D1	I	dc	Plug in	0.21
A1	I	ac	Plug in	0.23
AD1	I	ac-dc	Plug in	0.23

TABLE II. Operating characteristics.

PIN MS25455-	Coil data									Time - milliseconds maximum					
	Coil	Nominal			Max		1/ Max pick-up voltage			Op- erate 3/	Re- lease 4/	Contact Bounce			
		Volts 1/	Freq Hz	Ω Res	Volts	Amp	Nor- mal 2/	High temp test	Cont cur- rent test			Main		Aux	
												NO	NC	NO	NC
D1	X1, X2 Y1, Y2	28	dc	N/A	29	0.12	18	18	19.8	25	N/A	2	2	N/A	N/A
A1	X1, X2 Y1, Y2	115	400 5/	N/A	122	0.06	90	90	95	25	N/A	2	2	N/A	N/A
AD1	X1, X2	115	400 5/	N/A	122	0.06	90	90	95	25	N/A	2	2	N/A	N/A
	Y1, Y2	28	dc	N/A	29	0.12	18	18	19.8	25	N/A	2	2	N/A	N/A

1/ CAUTION: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.

2/ Over the temperature range.

3/ With nominal coil voltage.

4/ From nominal coil voltage.

5/ MS25455-A1 and -AD1 ac coils may be used on 60 Hz if maximum ambient temperature is limited to +85°C (coil current: 0.066 ampere maximum).

TABLE III. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operat- ing cycles $\times 10^3$	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/				See appro- priate notes	
		Main		Aux		Main		Aux		Main		Aux			
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz		
Resistive	100	5	5			5	4								
Inductive	100														
Inductive	20	3	3			3	2								
Motor	100	1.5	1.5			1.5	1								
Lamp	100	0.8	0.8			0.8	0.6								
Transfer load														2/	
Mechanical life reduced current	400	1.25	1.25			1.25	1								
Mixed loads		Applicable per specification MIL-PRF-6106													

1/ Absence of value indicates relay is not rated for 3-phase application.

2/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

MS25455J

Environmental characteristics.

Temperature range	-70°C to +125°C
Max altitude rating	80,000 ft
Shock G-level	50 g's
Duration	11 ms
Max duration contact opening	10 μs
Vibration - sinusoidal (see chart below)	
G-level	10 g's
Frequency range	5-1,500 Hz
Acceleration	15 g's

Electrical characteristics.

Insulation resistance:

Initial: 100 megohms.

After life or environmental tests: 50 megohms.

Dielectric strength (sea level).

	<u>Initial</u>	<u>After life tests</u>
Coil to case	1,000 V rms	1,000 V rms
Aux contacts		
All other points	1,000 V rms	1,000 V rms

Dielectric strength (altitude).

	(When mounted in mating socket)
Coil to case	<u>80,000 ft</u> 500 V rms
Aux contacts	
All other points	500 V rms

Max contact voltage drop:

Initial: 0.150 volt.

After life test: 0.175 volt.

Overload current	20 amperes.
Rupture current	25 amperes.
Duty rating	Continuous.
RFI specification	MIL-STD-461

(Applicable to coil circuits of ac operated relays).

MS25455J

Conformance inspection.

Performance of groups B and C tests are not applicable.

Group A acceptance reports shall be submitted to the preparing activity on a yearly basis in order to retain qualification for this military specification sheet.

Qualification by similarity: See [MIL-PRF-6106](#).

Referenced documents. In addition to [MIL-PRF-6106](#), this document references the following:
[MIL-STD-461](#) [SAE-AMS3332](#) [ASTM-B488](#)

Custodians:

Navy - AS

Air Force - 85

DLA - CC

Preparing activity:

DLA - CC

(Project 5945-2020-055)

Review activity:

Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.dla.mil/>.