

User activities: Army -
Navy -
Air Force -

Review activities: Army -
Navy - EC
Air Force - 11

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

INACTIVE FOR NEW DESIGN AFTER 5 JUN 87 NO SUPERSEDING STANDARD (FOR NEW DESIGN USE MIL-R-6106/51)		FED. SUP CLASS 5945																																																	
12 PINS, .0625 ± .0010 DIA 4 PINS .040 ± .001 DIA (X1, X2, Y1, Y2) GOLD PLATED, MIL-G-45204, TYPE II, CLASS I, UNDERPLATING, NICKEL 50 TO 150 MICROINCHES THICK		<table border="1"> <thead> <tr> <th>Inches</th> <th>mm</th> </tr> </thead> <tbody> <tr><td>.000</td><td>0.00</td></tr> <tr><td>.001</td><td>0.03</td></tr> <tr><td>.005</td><td>0.13</td></tr> <tr><td>.040</td><td>1.02</td></tr> <tr><td>.047</td><td>1.19</td></tr> <tr><td>.062</td><td>1.57</td></tr> <tr><td>.0625</td><td>1.59</td></tr> <tr><td>.093</td><td>2.36</td></tr> <tr><td>.145</td><td>3.86</td></tr> <tr><td>.147</td><td>3.73</td></tr> <tr><td>.203</td><td>5.16</td></tr> <tr><td>.290</td><td>7.37</td></tr> <tr><td>.344</td><td>8.74</td></tr> <tr><td>.375</td><td>9.53</td></tr> <tr><td>.435</td><td>11.05</td></tr> <tr><td>.580</td><td>14.73</td></tr> <tr><td>.725</td><td>18.42</td></tr> <tr><td>.870</td><td>22.10</td></tr> <tr><td>1.500</td><td>38.10</td></tr> <tr><td>1.562</td><td>39.67</td></tr> <tr><td>1.812</td><td>46.02</td></tr> <tr><td>1.844</td><td>46.84</td></tr> <tr><td>2.187</td><td>55.55</td></tr> </tbody> </table>		Inches	mm	.000	0.00	.001	0.03	.005	0.13	.040	1.02	.047	1.19	.062	1.57	.0625	1.59	.093	2.36	.145	3.86	.147	3.73	.203	5.16	.290	7.37	.344	8.74	.375	9.53	.435	11.05	.580	14.73	.725	18.42	.870	22.10	1.500	38.10	1.562	39.67	1.812	46.02	1.844	46.84	2.187	55.55
Inches	mm																																																		
.000	0.00																																																		
.001	0.03																																																		
.005	0.13																																																		
.040	1.02																																																		
.047	1.19																																																		
.062	1.57																																																		
.0625	1.59																																																		
.093	2.36																																																		
.145	3.86																																																		
.147	3.73																																																		
.203	5.16																																																		
.290	7.37																																																		
.344	8.74																																																		
.375	9.53																																																		
.435	11.05																																																		
.580	14.73																																																		
.725	18.42																																																		
.870	22.10																																																		
1.500	38.10																																																		
1.562	39.67																																																		
1.812	46.02																																																		
1.844	46.84																																																		
2.187	55.55																																																		
		(G) denotes changes																																																	
P.A AIR FORCE - 85 Other Cust Navy - AS	International Interest	TITLE RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE I, MAGNETIC LATCH, SOCKET MOUNTED, HERMETICALLY SEALED	MILITARY STANDARD MS25461																																																
Procurement Specification MIL-R-6106		SUPERSEDES	PAGE 1 OF 5																																																

DD FORM 672 1 MAY 73

(Coordinated) previous editions of this form are obsolete.

5945-0780

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

APPROVED 1 Nov 1960 REVISED 6 JUN 87 29 APR 88

FED. SUP CLASS
5945

is military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - EC
Navy - EC
Air Force - 11

User activities: Army -
Navy -
Air Force -

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ± 0.010 (0.25 mm).
4. Terminal numbers need not appear on relay headers provided there is affixed to the relay a suitable legible circuit diagram that permanently and positively identifies each terminal location specified herein.
5. The use of diodes on ac relays is optional. Actual application must be shown on label.
6. Relay is magnetically latched in both positions. Caution note to observe polarity must appear on relays with dc coils.
7. In the event of conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.
8. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.
9. Shock, vibration, and acceleration requirements application with coils de-energized.
10. Pins to be perpendicular to header surface within one degree.

⑥

TABLE I. Dash numbers and characteristics.

Dash number MS 25461-	Type	Coil	Terminal type	Max weight in pounds
D1	I	dc	Plug in	0.40
A1	I	ac	Plug in	0.42

REVISED ⑥ FOR CHANGES SEE PAGES 1,2, AND 3

APPROVED 1 Nov 1960

P.A AIR FORCE - 85 Other Cust Navy - AS	International Interest	TITLE RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE I, MAGNETIC LATCH, SOCKET MOUNTED, HERMETICALLY SEALED	MILITARY STANDARD MS25461
Procurement Specification MIL-R-6106		SUPERSEDES:	PAGE 2 OF 5

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - EC
Navy - EC
Air Force - II

Usage activities: Army -
Navy -
Air Force -

PA
AIR FORCE -85
Other Cust
NAVY-AS

International
Interest

TITLE

RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT,
TYPE I, MAGNETIC LATCH, SOCKET MOUNTED,
HERMETICALLY SEALED

MILITARY STANDARD

MS25461

Procurement Specification
MIL - R - 6106

SUPERSEDES:

PAGE 3 OF 5

DD FORM 672
1 MAY 73

(Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

TABLE II. Operating characteristics.

MS part no. MS25461-	Coil data										Time - (milliseconds max/min)						
	Coil	Nominal			Max		Max pick-up voltage			Drop - out voltage	Operate 3/	Release 4/	Contact bounce				
		Volts 1/	Freq. Hz	Res Ω	Volts	Amperes	Normal 2/	High temp test					Cont current test				
D1	X1, X2 Y1, Y2	28	dc	N/A	29	0.17	18	18	19.8	N/A	25	N/A	2	2	NO	NC	NC
A1	X1, X2 Y1, Y2	115	400 5/	N/A	122	0.07	90	90	95	N/A	25	N/A	2	2			

1/ CAUTION: Use of any coil voltage less than nominal coil voltage will compromise the operation of the relay.
2/ Over the temperature range.
3/ With nominal coil voltage.
4/ From nominal coil voltage.
5/ MS25461-A1 may be used on 60 Hz if maximum ambient temperature is limited to +85°C (maximum coil current shall be 0.077 amperes).

FED. SUP CLASS
5945

APPROVED 1 NOV 1980 REVISED ⑥ FOR CHANGES SEE PAGES 1, 2, AND 3

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - EC
Navy - EC
Air Force - II

User activities: Army -
Navy -
Air Force -

TABLE III. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles X 10 ³	28 V dc		115 V ac, 1 phase		115/200 V ac, 3 phase 1/				See appropriate notes
		Main	Aux	Main	Aux	Main	Aux	Main	Aux	
		NO	NC	NO	NC	400 Hz	160 Hz	400 Hz	160 Hz	
Resistive	100	10	10	10	6			10	6	
Inductive	100									
Inductive	20	6	6	10	4			10	4	
Motor	100	4	4	4	3			4	3	
Lamp	100	2	2	2	1.5			2	1.5	
Transfer load										2/
Mechanical life reduced current	400	2.5	2.5	2.5	2			2.5	2	
Intermittent current		Applicable per specification								

1/ Absence of value indicates relay is not rated for 3-phase applications.
2/ Transfer load indicates relay suitable for transfer between unsynchronized ac power supplies at rating indicated.

FED. SUP CLASS
5945

P.A. AIR FORCE - 85 Other Cust NAVY - AS	International Interest	TITLE RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE I, MAGNETIC LATCH, SOCKET MOUNTED, HERMETICALLY SEALED	MILITARY STANDARD
Procurement Specification MIL - R - 6106	SUPERSEDES:	MS 25461	PAGE 4 OF 5

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

APPROVED 1 NOV 1960 REVISED ① FOR CHANGES SEE PAGES 1, 2, AND 3

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - EC
Navy - EC
Air Force - II

User activities: Army -
Navy -
Air Force -

Environmental characteristics Temperature range -70°C to +125°C Max altitude rating 80,000 ft Shock G-level 50 G Duration 11 ms Max duration contact opening 10 μs Vibration - sinusoidal 10 G G-level 10 G Frequency range 5 - 1500 Hz Acceleration 16 G		Electrical characteristics Insulation resistance, initial 100 megohms After life or environmental tests 50 megohms Dielectric strength initial (sea level) Initial After life tests Coil to case 1,000 V rms 1,000 V rms Aux contacts All other points 1,500 V rms 1,125 V rms Dielectric strength (altitude) Coil to case 80,000 ft 250 V rms Aux contacts All other points 350 V rms Max contact drop initial 0.150 volt After life test 0.175 volt Overload current 40 amperes dc, 60 amperes ac, 50 amperes dc, 80 amperes ac Rupture current Continuous Duty rating MIL-STD-461 RFI specification (Applicable to coil circuits of ac operated relays) Quality conformance inspection Performance of groups B and C tests are not applicable.	
P.A AIR FORCE - 85 Other Cust NAVY - AS		TITLE RELAYS, ELECTROMAGNETIC, 10 AMPERES, 4 PDT, TYPE I, MAGNETIC LATCH, SOCKET MOUNTED, HERMETICALLY SEALED	
MIL-R-6106		MILITARY STANDARD MS25461	
SUPSEDES:		PAGE 5 OF 5	

FED. SUP CLASS
5945

APPROVED N 1 NOV 1980 REVISED ③ FOR CHANGES SEE PAGES 1, 2, AND 3