

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any right or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

		FED. SUP CLASS 5935	
<p>PART SECTION A-A</p>		<p>OF FORMING SHOWN IN SECTION A-A TIONAL. DIMENSIONS SHOWN WHEN FORMING IS USED</p>	
<p>FEMALE</p>			
<p>1. ALL DIMENSIONS IN INCHES. 2. UNTOLERANCED DECIMAL DIMENSIONS SHALL BE SUBJECT TO A PLUS OR MINUS 0.005 INCH TOLERANCE. 3. THE CONFIGURATION AND CRITICAL DIMENSIONS NECESSARY FOR INTERCHANGEABILITY AND MATING OF THE PLUG AND RECEPTACLE ARE THE SAME AS THOSE DESCRIBED IN AMERICAN STANDARD C73.1-1957. 4. THIS IS A DESIGN STANDARD. NOT TO BE USED AS A PART NUMBER.</p>			
P.A. Other Cust	CE ARDC DOCKS	TITLE CONNECTOR, PLUG, ELECTRICAL AND CONNECTOR, RECEPTACLE, ELECTRICAL, 3 POLE, 3 WIRE, 30 AMPERE, 250 VOLTS	MILITARY STANDARD <b>MS 27014</b>
PROCUREMENT SPECIFICATION W-C-596, STYLE 8		SUPERSEDES:	SHEET 1t OF 1