

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government hereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have furnished, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Department of Defense. It is mandatory for use by all other military activities as required in applicable instructions.

FED. SUP CLASS 6210		REVISED (A) 13 OCT 61 (B) 1 FEB 62 (C) 25 FEB 69 (D) 1 MAY 1975	
<p>NOTE 1. 3 LUGS, OR A CONTINUOUS INSIDE LIP REQUIRED.</p> <p>NOTE 2. SPRING, CORROSIVE RESISTANT. PULL OF 4 1/4 ± 1/4 POUNDS REQUIRED TO STRETCH SPRING 1 INCH. HOOKS SHALL ENGAGE ON HOOD HOOKS.</p> <p>DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMAL ±0.016, ANGLES ±1°.</p> <p>MATERIAL: SHEET ALUMINUM NOT LESS THAN 0.035 INCH THICK.</p> <p>THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</p>			
<p>P.A. AIR FORCE Other Cust</p>		<p>TITLE: HOOD, BLACKOUT - MEDIUM INTENSITY RUNWAY LIGHT</p>	
<p>PROCUREMENT SPECIFICATION MIL-L-7082</p>		<p>SUPERSEDES:</p>	
<p>FORM 1 SEP 65 672-1 (limited coordination)</p>		<p>PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.</p>	
<p>MILITARY STANDARD MS27038 (USAF)</p>		<p>SHEET 1 OF 1</p>	