

NOTE:

MATERIAL: SUFFIX "C": CORROSION RESISTING STEEL. NO SUFFIX: COMBINATION OF ALUMINUM ALLOY AND CORROSION RESISTING STEEL. SEE MS STANDARDS LISTED ON SHEET 1 FOR MATERIAL SPECIFICATIONS.

THESE PARTS ARE FOR USE WITH MIL-H-27267 HOSE.

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON THE DATE OF INVITATION FOR BID.

(d) IF REQUIRED, LOCKWIRE HOLES TO BE DRILLED IN ACCORDANCE WITH AS1043 AND SUFFIX "L" ADDED TO PART NUMBER. EXAMPLE: MS27053-8CL.

THE MS PART NUMBER AND MANUFACTURER'S PART NUMBER SHALL BE MARKED ON

A REMOVABLE TAG SECURELY ATTACHED TO THE FITTING.

(b) SWIVEL NUT AND CONE SEAT OF NIPPLE SHALL MATE WITH MS33656-3 FITTING, THE REMAINING PORTION OF THE ASSEMBLY SHALL MATE WITH

MIL-H-27267-4 HOSE.

© MS27053-3C INACTIVE FOR DESIGN AFTER 2 MAY 1966, USE ONLY FOR REPLACEMENT OF IDENTICAL ITEMS IN EXISTING MILITARY EQUIPMENT.

USE MS27053-3/MC FOR DESIGN.

(C) "A" IS THE DIMENSION BETWEEN THE HOSE END OF FITTING AND THE FREE END OF THE INSERT AT ITS CENTERLINE WHEN THE SOCKET IS ASSEMBLED ON THE NIPPLE.

APPROVED I TITLE **ADAPTER** ASSY, FLARED MILITARY STANDARD Air Force-11 (C) TUBE TO HOSE -STRAIGHT, Other Cust MS27053 -27272 SUPERSEDES MIL-F SHEET 2 OF 2

MIL-F-27272

DD | FORM 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE DESOLET

 a royalty free license under the following besed patents for the benefit of Manufacturers of the item either or for use in equipment to be delivered to the dovernment, (U.S. Piernt Nos. 21-33,507) 3,044,103; 3,055,689 : þ¢ NOTE:

SHEETS I AND

FOR CHANGES SEE

<u>ල</u>

REVISED

Sep 61

FED SUP CLASS 4730

DA TE