



| DASH NO. | INTEGRAL LIGHT |
|----------|----------------|
| -1       | RED            |
| -2       | WHITE          |

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS 1.008.

THE APERTURE AND ELECTRICAL CONNECTORS SHALL BE CENTERED WITH REFERENCE TO CASE CENTERLINES.

This standard has been approved by the Bureau (Department of the Navy) and the Department of the USAF and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

|  |   |   |
|--|---|---|
| P.A. USAF - 11                           | TITLE   | <b>MILITARY STANDARD</b><br><b>MS27202(ASG)</b> |
| Other Cust<br>Navy - Wep                 | INDICATOR, POSITION, LANDING GEAR, SYMBOL-INDICATING,<br>INTEGRALLY LIGHTED |   |
| PROCUREMENT SPECIFICATION<br>MIL-I-25931 | SUPERSEDES:   | SHEET 1 OF 1                                    |

APPROVED 14 Sept 64 REVISED