

FED. SUP CLASS
5945


STUD, THD. .190-32 UNF-2A
NUT, MS35650-305 T
WASHER, AN961-10
WASHER, MS35338-100
9 EACH REQUIRED

TERMINAL MARKING
LOCATION OPTIONAL

STUD, THD. .138-32 UNC-2A
NUT, MS35649-265 T
WASHER, MS35338-96
WASHER, AN961-6
2 EACH REQUIRED (ADDITIONAL
WASHER MAY BE
USED FOR
TERMINAL
SEAT)

.218 \pm .010 DIA
4 MOUNTING HOLES

NAMEPLATE



(H) CANCELLED AFTER 31 JULY, 1984
NO SUPERSEDING STANDARD

MS PART NUMBER	TYPE	COIL TYPE	TERMINAL TYPE	MOUNTING OR MATING SOCKET	AUXILIARY CONTACTS	MAX WEIGHT IN POUNDS
MS27221-D1	I	DC	STUD	FLANGE	N/A	1.7
MS27221-A1	I	AC	STUD	FLANGE	N/A	1.8
MS27221-A2	I	AC	STUD	FLANGE	N/A	1.8

(H) DENOTES CHANGES

P.A. USAF-85	International Interest	TITLE	RELAY, 50 AMP, 3PDT, HERMETICALLY SEALED, MECHANICALLY INTERLOCKED	MILITARY STANDARD
Other Cust Navy-AS				MS27221
Procurement Specification MIL-R-6106		SUPERSEDES:		SHEET 1 OF 1

DD FORM 672 1 SEP 63 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

User activities: Army
Navy
Air Force
EC
99,11
Reviewer activities: Army
Navy
Air Force

APPROVED 21 Apr 1964 REVISED (F) 17 JUNE 77 (G) 10 Dec 81 (H) 3 DEC 84