



BODY OF BASE SHALL
PASS THRU A RING
OF 1.098 DIAMETER

DASH NO	INITIAL WATTS	RATED VOLTS	RATED AVERAGE LAB LIFE	RATED INITIAL LUMENS	INITIAL EFFICIENCY LUMENS PER WATT	BURNING POSITION	FILAMENT SIZE
-1	120 ± 8	120	8000 HR	1180	9.8 ± 2	BASE DOWN TO HORIZONTAL	W - 9MM ± 0.9MM H - 8MM ± 0.8MM
-2	125 ± 8	120	6000 HR	1180	9.4 ± 2	BASE DOWN TO HORIZONTAL	W - 9MM ± 0.9MM H - 8MM ± 0.8MM

- 1 LAMP INACTIVE FOR PROCUREMENT AFTER 22 NOVEMBER 1966
-2 LAMP COMMERCIAL DESIGNATION IS 125A21P

UNLESS OTHERWISE SPECIFIED

DIMENSIONS IN INCHES

TOLERANCES: DECIMALS ± 0.16, ANGLES ± 0° - 30°

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION TO BID.

(B) CANCELLED - AFTER 20 JULY 1981 - NO SUPERSEDING DOCUMENT

P.A. AIR FORCE - II Other Cust	TITLE LAMP, INCANDESCENT, A-21 BULB, AIRPORT OBSTRUCTION MEDIUM PREFOCUS BULB	MILITARY STANDARD MS 27263 (USAF)
PROCUREMENT SPECIFICATION MIL - L - 6363	SUPERSEDES:	SHEET 1 OF 1

REVIEWERS:
AIR FORCE - II, 82

THIS STANDARD HAS BEEN APPROVED BY THE DEPARTMENT OF THE
AIR FORCE AND IS MANDATORY FOR USE BY THAT ACTIVITY. ALL OTHER
MILITARY ACTIVITIES ARE REQUIRED TO EMPLOY THIS STANDARD WHERE SUITABLE.

APPROVED 1 JULY 1963 REVISED (A) 22 NOV 1966 (B) 20 JULY 1981

U.S. GOVT. REPRODUCTION