

User activities: Army -  
Navy -  
Air Force -

Reviewer activities: Army - ML, AR  
Navy - EC, MC, OS  
Air Force - 11, 15, 17, 99  
DLA-ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS 5935																																														
<p>SEE DETAIL AA</p> <p>Q</p> <p>28° BSC</p> <p>80° BSC</p> <p>100° BSC</p> <p>120° BSC</p> <p>37° BSC</p> <p>3 PROJECTIONS</p> <p>KEYWAY 4 PLACES</p> <p>0.047 MAX</p> <p>L</p> <p>M</p> <p>J</p> <p>DISK</p> <p>-E-</p> <p>MARKING</p> <p>FLUTES OR KNURL</p> <p>FOR DETAILS OF CAP FRONT END CONFIGURATION SEE PROCUREMENT SPECIFICATION</p>	<p>0.047 MAX</p> <p>L</p> <p>M</p> <p>J</p> <p>DISK</p> <p>-E-</p> <p>MARKING</p> <p>FLUTES OR KNURL</p>																																													
<table border="1"> <thead> <tr> <th>SHELL SIZE</th> <th>J +.015 -.010</th> <th>L MAX</th> <th>M MIN</th> <th>Q MAX DIA</th> <th>T +.006 -.002 DIA</th> <th>X BSC DEG</th> <th>Y BSC DEG</th> <th>CC</th> </tr> </thead> <tbody> <tr> <td>8</td> <td rowspan="8">.222</td> <td rowspan="8">.562</td> <td rowspan="8">.312</td> <td>.719</td> <td rowspan="8">.078</td> <td>82°</td> <td>118°</td> <td>.004</td> </tr> <tr> <td>10</td> <td>.844</td> <td>72°</td> <td>128°</td> <td rowspan="8">.010</td> </tr> <tr> <td>12</td> <td>1.000</td> <td>68°</td> <td>132°</td> </tr> <tr> <td>14</td> <td>1.125</td> <td>66°</td> <td>134°</td> </tr> <tr> <td>16</td> <td>1.250</td> <td rowspan="4">70°</td> <td rowspan="4">130°</td> </tr> <tr> <td>18</td> <td>1.375</td> </tr> <tr> <td>20</td> <td>1.500</td> </tr> <tr> <td>22</td> <td>1.625</td> </tr> <tr> <td>24</td> <td>1.750</td> <td>74°</td> <td>126°</td> </tr> </tbody> </table>	SHELL SIZE	J +.015 -.010	L MAX	M MIN	Q MAX DIA	T +.006 -.002 DIA	X BSC DEG	Y BSC DEG	CC	8	.222	.562	.312	.719	.078	82°	118°	.004	10	.844	72°	128°	.010	12	1.000	68°	132°	14	1.125	66°	134°	16	1.250	70°	130°	18	1.375	20	1.500	22	1.625	24	1.750	74°	126°	<p>EXAMPLE OF PART NUMBER</p> <p>MS27352 B 12</p> <p>MS NO FINISH SHELL SIZE</p>
SHELL SIZE	J +.015 -.010	L MAX	M MIN	Q MAX DIA	T +.006 -.002 DIA	X BSC DEG	Y BSC DEG	CC																																						
8	.222	.562	.312	.719	.078	82°	118°	.004																																						
10				.844		72°	128°	.010																																						
12				1.000		68°	132°																																							
14				1.125		66°	134°																																							
16				1.250		70°	130°																																							
18				1.375																																										
20				1.500																																										
22				1.625																																										
24	1.750	74°	126°																																											
<p>INACTIVE FOR DESIGN AFTER 13 SEPTEMBER 1997</p> <p>INTERCHANGEABILITY RELATIONSHIP</p> <p>by the style are universally, functionally, interchangeable.</p> <p><b>(F) CANCELED - FOR PROCUREMENT USE MS27510 STYLE A</b></p> <p><b>(F) DENOTES CHANGES</b></p>																																														
<p>P.A. AF-85</p> <p>Other Cust ARMY - CR NAVY - AS</p>	<p>International Interest</p>	<p>TITLE CAP, PROTECTIVE, ELECTRICAL CONNECTOR PLUG, BAYONET COUPLING, SERIES II</p>				<p>MILITARY STANDARD</p> <p><b>MS27352</b></p>																																								
<p>Procurement Specification <b>MIL-C-38999</b></p>		<p>SUPERSEDES: <b>MS27352 (USAF)</b></p>				<p>PAGE 1 OF 1</p>																																								