



TABLE I

DASH NO.	LENGTH L ± .250 [ⓓ]
-1	6.000
(a) -2	9.000
-3	12.000

ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED.

ALL TOLERANCES ± .015 UNLESS OTHERWISE SPECIFIED.

[ⓓ] MATERIAL: A MOLDED ELASTOMER OR A SYNTHETIC FIBER MATERIAL (WOVEN OR BRAIDED). THE ABOVE DIMENSIONS ARE ALL APPLICABLE TO MOLDED MATERIALS. FOR FIBER MATERIALS, THE DIMENSIONS DO NOT APPLY, EXCEPT THAT THE FINISHED PRODUCT MUST FIT OVER .125 DOWEL PINS AT THE REQUIRED GAGE LENGTH AND MUST COMPLY WITH PERFORMANCE REQUIREMENTS OF THE PROCUREMENT SPECIFICATION.

[ⓓ] CLASS SHALL BE A, B, OR C, BASED ON THE APPLICABLE TEMPERATURE ENVIRONMENT. IDENTIFICATION SHALL BE IN ACCORDANCE WITH THE PROCUREMENT SPECIFICATION.

(a) DASH NO. -2 INACTIVE FOR DESIGN AFTER 20 JANUARY 1978. NO SUPERSEDING DASH NUMBER.

Review activities: USAF - 99
Army - AV

This military standard is approved by the Department of the Air Force and the Naval Air Systems Command and is mandatory for the use by these activities. All other military activities are required to employ this standard where suitable.

APPROVED 15 Dec 1965 REVISED A 18 Oct 1966 B 26 Feb 69 C 20 JAN 78 D 28 Jul 82

P.A. USAF - 11 Other Code NAVY - AS	TITLE LANYARD, FLUID TANK CAP	MILITARY STANDARD MS27380
PROCUREMENT SPECIFICATION MIL-C-38373	SUPERSEDES:	SHEET 1 OF 1