

Approved for public release; distribution is unlimited

FED. SUP CLASS  
5930

User activities: Air Force - 11

Review activities: Army - AV  
Navy - EC  
Air Force - 99  
DLA - ES

Inches	mm	Inches	mm
.005	0.13	.37	9.4
.008	0.20	.38	9.7
.012	0.30	.432	10.97
.020	0.51	.47	11.9
.03	0.8	.69	17.5
.060	1.52	1.10	27.9
.076	1.93	1.340	34.04
.130	3.30	1.370	34.80
.240	6.10	1.660	42.16
.25	6.4		

## NOTES:

1. Dimensions are inches.
- ② 2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is  $\pm 0.020$  (0.51 mm) for two place decimals and  $\pm 0.005$  (0.13 mm) for three place decimals.
- ④ 4. For hardware and terminal screw detail specifications, see appendix of MIL-S-3950.
5. All switches on this standard are designed so that the movement of the switch mechanism is opposite to that of the toggle lever.
6. Maximum weight is 0.20 pound.
- ⑦ 7. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.
- ⑧ 8. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.

APPROVED 19 April 1965 REVISED ① For changes see page 2.

P.A.  
Air Force - 85  
Other Cust  
Army - ER  
Navy - ASInternational  
Interchange

## TITLE

SWITCH, TOGGLE, FOUR POLE,  
ENVIRONMENTALLY SEALED

MILITARY STANDARD

MS27406

Procurement Specification  
MIL-S-3950

SUPERSEDES

PAGE 2 OF 3

User activity: Air Force - 11

 Review activities  
 Army - AV  
 Navy - EC  
 Air Force - 99  
 DLA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

P A Air Force - 85 Other Cust Army - ER Navy - AS		International Interest	TITLE  SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED		MILITARY STANDARD  MS27406																																																		
Procurement Specification MIL-S-3950			SUPERSEDES		PAGE 3 OF 3																																																		
Detail requirements: <table border="1"> <thead> <tr> <th rowspan="2">MS part number</th> <th colspan="3">Circuit with toggle lever in</th> <th colspan="3">Current capacity (amperes) 28 volts dc</th> <th colspan="3">Current capacity (amperes) 115 volts, 60 and 400 hertz ac</th> </tr> <tr> <th>Keying side</th> <th>Center</th> <th>Opposite keying side</th> <th>Lamp-load circuit</th> <th>Resistive circuit</th> <th>Inductive circuit</th> <th>Lamp-load circuit</th> <th>Resistive circuit</th> <th>Inductive circuit</th> </tr> </thead> <tbody> <tr> <td>MS27406-1</td> <td>1-2 4-5 12-3 7-8 On 10-11 7-8 On 11-12</td> <td>4-5 11-12</td> <td>2-3 5-6 8-9 On 11-12</td> <td>5</td> <td>20</td> <td>12</td> <td>4</td> <td>15</td> <td>15</td> </tr> <tr> <td>MS27406-2</td> <td>1-2 Mom. 4-5 12-3 7-8 on 10-11 7-8 On 11-12</td> <td>4-5 11-12</td> <td>2-3 5-6 8-9 On 11-12</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>MS27406-3</td> <td>1-2 Mom. 4-5 12-3 7-8 on 10-11 7-8 On 11-12</td> <td>4-5 11-12</td> <td>2-3 Mom. 5-6 8-9 on 11-12</td> <td>4</td> <td>18</td> <td>10</td> <td>2</td> <td>11</td> <td>8</td> </tr> </tbody> </table>							MS part number	Circuit with toggle lever in			Current capacity (amperes) 28 volts dc			Current capacity (amperes) 115 volts, 60 and 400 hertz ac			Keying side	Center	Opposite keying side	Lamp-load circuit	Resistive circuit	Inductive circuit	Lamp-load circuit	Resistive circuit	Inductive circuit	MS27406-1	1-2 4-5 12-3 7-8 On 10-11 7-8 On 11-12	4-5 11-12	2-3 5-6 8-9 On 11-12	5	20	12	4	15	15	MS27406-2	1-2 Mom. 4-5 12-3 7-8 on 10-11 7-8 On 11-12	4-5 11-12	2-3 5-6 8-9 On 11-12							MS27406-3	1-2 Mom. 4-5 12-3 7-8 on 10-11 7-8 On 11-12	4-5 11-12	2-3 Mom. 5-6 8-9 on 11-12	4	18	10	2	11	8
MS part number	Circuit with toggle lever in			Current capacity (amperes) 28 volts dc				Current capacity (amperes) 115 volts, 60 and 400 hertz ac																																															
	Keying side	Center	Opposite keying side	Lamp-load circuit	Resistive circuit	Inductive circuit	Lamp-load circuit	Resistive circuit	Inductive circuit																																														
MS27406-1	1-2 4-5 12-3 7-8 On 10-11 7-8 On 11-12	4-5 11-12	2-3 5-6 8-9 On 11-12	5	20	12	4	15	15																																														
MS27406-2	1-2 Mom. 4-5 12-3 7-8 on 10-11 7-8 On 11-12	4-5 11-12	2-3 5-6 8-9 On 11-12																																																				
MS27406-3	1-2 Mom. 4-5 12-3 7-8 on 10-11 7-8 On 11-12	4-5 11-12	2-3 Mom. 5-6 8-9 on 11-12	4	18	10	2	11	8																																														

FED. SUP CLASS  
5930

APPROVED 19 April 1965 REVISED (D) For changes see page 2

DD FORM 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE  
1 MAY 73