


NOTICE.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have furnished, furnished, or in any way applied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



FED. SUP CLASS
7690

MS PART NO.	FILE	DIMENSIONS
MS 27413		1 1/2 IN. W. 36 XD IG. O/A DIM.

NOTES: 1. The colors are in accordance with Federal Standard 595

- Background color, yellow number 23655
- Letters black color number 27038

2. The space between each printed legend shall be 1/4 inch. The perforations shall be 1/8 inch from the end of every two (2) labels and shall be perforated every 7 1/2 inches. A width tolerance of + or - 1/16 inch will be permitted. Material for label tape shall be in accordance with Military Specification MIL-T-9906.

3. This standard takes precedence over documents referenced herein.

4. Referenced documents shall be of the issue in effect on date of invitations for bid.

(B) Cancelled after 6 Apr 84
NO SUPERSEDING STANDARD

P.A. AIR FORCE: 84	TITLE	MILITARY STANDARD
Other Cust ARMY: GL NAVY: AS	LABEL, TAPE, PRESSURE SENSITIVE ADHESIVE	MS27413
Procurement Specification	SUPERSEDES:	SHEET 1 OF 1