


FED. SUP CLASS
5930

Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES

User activity: Air Force - 11

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.



APPROVED 15 May 1972 REVISED (A) 14 May 1974 (B) 25 Apr 1975 (C) 28 Sep 1987

P A Air Force - B5 Other Cust Army - ER Navy - AS	International Interest	TITLE SWITCH, TOGGLE, ONE POLE, ENVIRONMENTALLY SEALED, INTEGRATED WIRE TERMINALS	MILITARY STANDARD
			MS27784
Procurement Specification MIL-S-3950	SUPSEDES		PAGE 1 OF 3

FED SUP CLASS
5930

User activity: Air Force - 11

Review activities:
Army - AV
Navy - EC
Air Force - 99
DLA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Inches	mm	Inches	mm
.005	0.13	.38	9.7
.008	0.20	.432	10.97
.012	0.30	.469	11.91
.020	0.51	.47	11.9
.03	0.8	.635	16.13
.060	1.52	.69	17.5
.076	1.93	1.270	32.26
.240	6.10	1.662	42.21

NOTES:

- Dimensions are inches.
- Metric equivalents are given for general information only.
- Unless otherwise specified, tolerance is $\pm .020$ (0.51 mm) for two place decimals and $\pm .005$ (0.13 mm) for three place decimals.
- For hardware detail specifications see appendix of MIL-S-3950.
- Ⓒ Contact installing/removal tool in accordance with M81969/14-02.
- Ⓒ Grommet sealing plug, in accordance with MS27488A20.
- The sealing grommet shall seal on a smooth wire insulation of .040 (1.02 mm) to .083 (2.11 mm) diameters.
- Ⓒ Terminal shall adequately accept a wire contact within dimensional limits of M39029/1-101.
- The terminal end of switch shall be color coded red to indicate contact size.
- Direction of internal mechanism movement is opposite to the direction of the toggle movement.
- Sealing plugs may be used in nonfunctional grommet holes.
- Maximum weight is .09 pound.
- Ⓒ In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.
- Ⓒ Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.

REVISED Ⓒ for changes see page 2

APPROVED 15 May 1972

P A Air Force - 85 Other Cust Army - ER Navy - AS	International Interest	TITLE SWITCH, TOGGLE, ONE POLE, ENVIRONMENTALLY SEALED, INTEGRATED WIRE TERMINALS	MILITARY STANDARD MS27784
Procurement Specification MIL-S-3950	SUPERSEDES	PAGE 2 OF 3	

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - AV, Navy - EC, Air Force - 99, DLA - ES

User activity: Air Force - 11

FED SUP CLASS
5930

Detail requirements:

MS part number	Circuit with toggle lever in		Current capacity (amperes) 28 volts dc			Current capacity (amperes) 115 volts, 60 and 400 hertz ac			
	Keying side	Center	Opposite keying side	Lamp-load circuit	Resistive circuit	Inductive circuit	Lamp-load circuit	Resistive circuit	Inductive circuit
MS27784-21	1-2 On	Off	2-3 On						
MS27784-22	Off	None	2-3 On	5	7.5	7.5	3	7.5	7.5
MS27784-23	1-2 On	None	2-3 On						
MS27784-24	None	Off	2-3 On						
MS27784-25	None	Mon. off	2-3 On						
MS27784-26	1-2 Mom. on	None	2-3 On						
MS27784-27	1-2 Mom. on	Off	2-3 Mom. on						
MS27784-28	1-2 Mom. on	Off	None						
MS27784-29	Mom. off	None	2-3 On	4	7.5	7.5	2	7.5	7
MS27784-30	1-2 Mom. on	None	Off						
MS27784-31	1-2 Mom. on	Off	2-3 On						
MS27784-32	None	On 1-2	2-3 Mom. on						
MS27784-33	None	On 1-2	2-3 On	5	7.5	7.5	3	7.5	7.5

Test requirements:

Test shall be performed in accordance with MIL-S-3950 except:

- a. During all tests, switches shall be fully wired with appropriate wire and terminal contacts.
- b. Contact voltage drop - the contact voltage drop with two terminals and the switch contact in series shall not exceed 8 millivolts measured from one wire contact through the contacts to the other wire contacts.

P A Air Force - 85 Other Cust Army - ER Navy - AS	International Interest	TITLE SWITCH, TOGGLE, ONE POLE, ENVIRONMENTALLY SEALED, INTEGRATED WIRE TERMINALS	MILITARY STANDARD MS27784
Procurement Specification MIL-S-3950	SUPERSEDES	PAGE 3 OF 3	