


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.



Ⓒ Denotes changes

P A Air Force - B5 Other Cust Army - ER Navy - AS	International Interest	TITLE SWITCH, TOGGLE, TWO POLE, ENVIRONMENTALLY SEALED, INTEGRATED WIRE TERMINALS	MILITARY STANDARD MS27785
Procurement Specification MIL-S-3950		SUPERSEDES	PAGE 1 OF 3

User activity Air Force - 11

Review activities:
Army - AV
Navy - EC
Air Force - 99
OLA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

FED SUP CLASS
5930

Inches	mm	Inches	mm
.005	0.13	.38	9.7
.008	0.20	.432	10.97
.012	0.30	.469	11.91
.020	0.51	.47	11.9
.03	0.8	.69	17.5
.060	1.52	.910	23.11
.076	1.93	1.340	34.04
.240	6.10	1.706	43.33

NOTES:

1. Dimensions are inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is $\pm .020$ (0.51 mm) for two place decimals and $\pm .005$ (0.13 mm) for three place decimals.
4. For hardware detail specifications see appendix of MIL-S-3950.
5. Contact installing/removal tool in accordance with M81969/14-02.
6. Grommet sealing plug, in accordance with MS27488A20.
7. The sealing grommet shall seal on a smooth wire insulation of .040 (1.02 mm) to .083 (2.11 mm) diameters.
8. Terminal shall adequately accept a wire contact within dimensional limits of M39029/1-101.
9. The terminal end of switch shall be color coded red to indicate contact size.
10. Direction of internal mechanism movement is opposite to the direction of the toggle movement.
11. Sealing plugs may be used in nonfunctional grommet holes.
12. Maximum weight is .12 pound.
13. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.
14. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this standard to the extent specified herein.

APPROVED 15 May 1972 REVISED (C) For changes see page 2

P A Air Force - 85 Other Cust Army - ER Navy - AS	International Interest	TITLE SWITCH, TOGGLE, TWO POLE, ENVIRONMENTALLY SEALED, INTEGRATED WIRE TERMINALS	MILITARY STANDARD
			MS27785
Procurement Specification MIL-S-3950		SUPERSEDES	PAGE 2 OF 3

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

User activity: Air Force - 11

Review activities: Army - AV
Navy - EC
Air Force - 99
DLA - ES

P A		International interest	TITLE	MILITARY STANDARD		
Air Force - 85 Other Cust Army - ER Navy - AS				MS27785		
Procurement Specification MIL-S-3950			SUPERSEDES		PAGE 3 OF 3	
Detail requirements						
MS part number	Circuit with toggle lever in		Current capacity (amperes) 28 volts dc		Current capacity (amperes) 115 volts, 60 and 400 hertz ac	
	Keying side	Center	Opposite keying side	Lamp-load circuit		Resistive circuit
MS27785-1	1-2 On 4-5	1-2 On 5-6	2-3 On 5-6	7	7.5	7.5
MS27785-2	Hom.	1-2 On 4-5	2-3 On 5-6			
MS27785-3	Hom.	1-2 On 4-5	2-3 On 5-6	5	7.5	7.5
MS27785-21	1-2 On 4-5	Off	2-3 On 5-6			
MS27785-22	Off	None	2-3 On 5-6			
MS27785-23	1-2 On 4-5	None	2-3 On 5-6	7	7.5	7.5
MS27785-24	None	Off	2-3 On 5-6			
MS27785-25	None	Hom. off	2-3 On 5-6			
MS27785-26	Hom.	None	2-3 On 5-6			
MS27785-27	Hom.	Off	2-3 On 5-6			
MS27785-28	Hom.	Off	None			
MS27785-29	Hom. off	None	2-3 On 5-6	5	7.5	7.5
MS27785-30	Hom.	None	Off			
MS27785-31	1-2 on 4-5	Off	2-3 on 5-6			
MS27785-32	None	1-2 On 4-5	2-3 On 5-6			
MS27785-33	None	1-2 On 4-5	2-3 On 5-6	7	7.5	7.5
Test requirements:						
Test shall be performed in accordance with MIL-S-3950 except:						
a. During all tests, switches shall be fully wired with appropriate wire and terminal contacts.						
b. Contact voltage drop - the contact voltage drop with two terminals and the switch contact in series shall not exceed 8 millivolts measured from one wire contact through the contacts to the other wire contacts.						

FED SUP CLASS
5930

APPROVED 15 May 1972 REVISED (C) For changes see page 2.