



MS27789D

## LOCKING COMBINATIONS














<p>A</p>  <p>LOCKED IN THREE POSITIONS</p>	<p>B</p>  <p>LOCKED IN CENTER AND DOWN POSITIONS (KEYING SIDE)</p>	<p>D</p>  <p>LOCKED OUT OF CENTER POSITION</p>	<p>E</p>  <p>LOCKED IN CENTER POSITION</p>
<p>F</p>  <p>LOCKED IN UP POSITION (OPPOSITE KEYING)</p>	<p>G</p>  <p>LOCKED IN DOWN POSITION (KEYING SIDE)</p>	<p>H</p>  <p>LOCKED OUT OF CENTER AND DOWN POSITION (KEYING SIDE)</p>	<p>J</p>  <p>LOCKED OUT OF CENTER AND UP POSITION (OPPOSITE KEYING)</p>
<p>K</p>  <p>LOCKED IN CENTER AND UP POSITION (OPPOSITE KEYING)</p>	<p>L</p>  <p>LOCKED OUT OF DOWN POSITION (KEYING SIDE)</p>	<p>M</p>  <p>LOCKED OUT OF AND INTO UP POSITION (OPPOSITE KEYING)</p>	<p>N</p>  <p>LOCKED OUT OF UP POSITION (OPPOSITE KEYING)</p>
	<p>P</p>  <p>LOCKED OUT OF AND INTO DOWN POSITION (KEYING SIDE)</p>	<p>FIGURES A THRU P DO NOT REPRESENT DETAILS OF CONSTRUCTION. THEY SCHEMATICALLY ILLUSTRATE LOCKING CONFIGURATIONS AND MOMENTARY POSITIONS</p>	

FIGURE 1 Dimensions and configuration- Continued

## MS27789D

Inches	mm	Inches	mm
.005	0.13	.432	10.97
.008	0.20	.469	11.91
.012	0.30	.47	11.9
.020	0.51	1.05	26.7
.060	1.52	1.140	28.96
.076	1.93	1.340	34.04
.38	9.7	1.660	42.16
.42	10.7	1.706	43.33

## NOTES:

1. Dimensions are inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is  $\pm .020$  (0.51 mm) for two place decimals and  $\pm .005$  (0.13 mm) for three place decimals.
4. For hardware detail specifications see appendix of MIL-DTL-3950.
5. Contact installing/removal tool in accordance with MIL-I-81969.
6. Grommet sealing plug in accordance with MS27488A20.
7. Sealing plugs may be used in nonfunctional grommet holes.
8. Sealing grommet shall seal on a smooth wire insulation of .040 (1.02 mm) to .083 (2.11 mm)
9. Terminal shall adequately accept a wire contact within dimensional limits of SAE-AS39029.
10. The terminal end of switch shall be color coded red to indicate contact size.
11. Direction of internal mechanism movement is opposite to the direction of the toggle movement.
12. Part number example: MS27789-21A ( locking combination 'A')
13. In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.

FIGURE1. Dimensions and configuration- Continued

## TEST REQUIREMENTS:

Test shall be performed in accordance with MIL-DTL-3950 except:

During all tests, switch shall be fully wired with appropriate wire and terminal contacts.

Contact voltage drop- the contact voltage drop with two terminals and the switch contact in series shall not exceed 8 millivolts measured from one wire contact through the contacts to the other wire contacts.

## DETAIL REQUIREMENTS:

Locking arrangement: Positive locking shall be accomplished and shall prevent motion of the toggle lever until the locking mechanism is manually released.

The force required to release the locking mechanism shall be 3 to 5 pounds.

The locking means at the top of the toggle bushing shall be capable of withstanding a torque of 20 inch-pounds applied in both directions immediately following the humidity test.

Weight: .227 pound maximum.

## MS27789D

MS part No.	Available locking combinations	Circuit with Toggle Lever In			Current capacity (amperes) 28 volts DC			Current capacity(amperes) 115 volts, 60 and 400 Hertz AC		
		Keying side	center	Opposite keying side	Lamp-Load circuit	Resistive circuit	Inductive circuit	Lamp-Load circuit	Resistive circuit	Inductive circuit
MS27789-1	ALL	1-2 4-5 7-8 on 10-11	2-3 4-5 7-8 on 11-12	2-3 5-6 8-9 On 11-12	5	7.5	7.5	4	7.5	7.5
MS27789-2	E, F, K, L, M, N	1-2 Mom. 4-5 7-8 on 10-11	2-3 4-5 7-8 on 11-12	2-3 5-6 8-9 on 11-12	4	7.5	7.5	2	7.5	7.5
MS27789-3	E, L, N	1-2 Mom. 4-5 7-8 on 10-11	2-3 4-5 7-8 on 11-12	2-3 Mom. 5-6 8-9 on 11-12						
MS27789-21	ALL	1-2 7-8 4-5 on 10-11	Off	2-3 8-9 8-9 on 11-12	5	7.5	7.5	4	7.5	7.5
MS27789-22	D, F, G	Off	None	2-3 8-9 5-6 on 11-12						
MS27789-23	D, F, G	1-2 Mom. 7-8 4-5 on 10-11	None	2-3 8-9 5-6 on 11-12						
MS27789-24	E, F, K, M	None	Off	2-3 8-9 5-6 on 11-12						
MS27789-25	F	None	Mom. Off	2-3 8-9 5-6 on 11-12	4	7.5	7.5	2	7.5	7.5
MS27789-26	F	1-2 Mom. 7-8 4-5 on 10-11	None	2-3 8-9 5-6 on 11-12						
MS27789-27	E, L, N	1-2 Mom. 7-8 4-5 on 10-11	Off	2-3 8-9 5-6 on 11-12						
MS27789-28	E	1-2 Mom. 7-8 4-5 on 10-11	Off	None						
MS27789-29	F	Mom. Off	None	2-3 8-9 5-6 on 11-12						
MS27789-30	F	1-2 Mom. 7-8 4-5 on 10-11	None	Off						
MS27789-31	E, F, K, L, M, N	1-2 Mom. 7-8 4-5 on 10-11	off	2-3 8-9 5-6 on 11-12						
MS27789-32	E	None	1-2 7-8 4-5 on 10-11	2-3 Mom. 8-9 5-6 on 11-12						
MS27789-33	E, F, K, M	None	1-2 7-8 4-5 On 10-11	2-3 8-9 5-6 on 11-12	5	7.5	7.5	4	7.5	7.5

## Referenced documents

MIL-DTL-3950

MIL-I-81969

MS27488

SAE-AS39029

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

## Custodians:

Army – CR

Navy - AS

Air Force - 11

DLA – CC

## Preparing activity

DLA -CC

(Project 5930-2005-003)

MS27789D

Review activities

Army – AR, AV, CR4

Navy – EC, MC

Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://assist.daps.dla.mil/>