

REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS
IFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN TH
SIS SPECIFIED IN THE SOLICITATION [MIL-S-8373]

IS APPROVED FOR USE BY all Regiments and Agencies
of Defense

PART NO. EIGHTEEN SIDE		CENTRE OF SWITCH OR TOGGLE LEVER MAXIMUM DIMENSIONS (EACH SIDE) ARE NOT EXCEEDED		Form Approved OMB No 0704-018B																																																													
NOTES 1 Dimensions are in inches 2 Metric equivalents are given for general information only 3 Unless otherwise specified, tolerance is + .020 (.51 mm) for two place decimals and + .005 (.13 mm) for three place decimals 4 For hardware detail specifications, see appendix of MIL-S-8373. 5 Configuration of switch case is optional provided maximum dimensions specified are not exceeded																																																																	
<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: right;">Inches</td> <td style="text-align: right;">MM</td> </tr> <tr> <td style="text-align: right;">.030</td> <td style="text-align: right;">.76</td> </tr> <tr> <td style="text-align: right;">.04</td> <td style="text-align: right;">1.02</td> </tr> <tr> <td style="text-align: right;">.055</td> <td style="text-align: right;">1.40</td> </tr> <tr> <td style="text-align: right;">.07</td> <td style="text-align: right;">1.78</td> </tr> <tr> <td style="text-align: right;">.10</td> <td style="text-align: right;">2.54</td> </tr> <tr> <td style="text-align: right;">.175</td> <td style="text-align: right;">4.45</td> </tr> <tr> <td style="text-align: right;">.25</td> <td style="text-align: right;">6.35</td> </tr> <tr> <td style="text-align: right;">.27</td> <td style="text-align: right;">6.86</td> </tr> <tr> <td style="text-align: right;">.31</td> <td style="text-align: right;">7.87</td> </tr> <tr> <td style="text-align: right;">.42</td> <td style="text-align: right;">10.67</td> </tr> <tr> <td style="text-align: right;">.535</td> <td style="text-align: right;">13.59</td> </tr> <tr> <td style="text-align: right;">.575</td> <td style="text-align: right;">14.61</td> </tr> <tr> <td style="text-align: right;">.640</td> <td style="text-align: right;">16.26</td> </tr> </table>						Inches	MM	.030	.76	.04	1.02	.055	1.40	.07	1.78	.10	2.54	.175	4.45	.25	6.35	.27	6.86	.31	7.87	.42	10.67	.535	13.59	.575	14.61	.640	16.26																																
Inches	MM																																																																
.030	.76																																																																
.04	1.02																																																																
.055	1.40																																																																
.07	1.78																																																																
.10	2.54																																																																
.175	4.45																																																																
.25	6.35																																																																
.27	6.86																																																																
.31	7.87																																																																
.42	10.67																																																																
.535	13.59																																																																
.575	14.61																																																																
.640	16.26																																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2" style="text-align: left; padding: 2px;">CANCELED MS PART NUMBER</th> <th rowspan="2" style="text-align: left; padding: 2px;">SUBSTITUTE MS PART NUMBER</th> <th colspan="4" style="text-align: center; padding: 2px;">CIRCUITS MADE WITH TOGGLE LEVER IN</th> <th rowspan="2" style="text-align: left; padding: 2px;">OPPOSITE</th> </tr> <tr> <th style="text-align: center; padding: 2px;">KEYING SIDE</th> <th style="text-align: center; padding: 2px;">CENTER POSITION</th> <th style="text-align: center; padding: 2px;">KEYING SIDE</th> <th style="text-align: center; padding: 2px;">OPPOSITE</th> </tr> <tr> <th style="text-align: left; padding: 2px;">1/</th> <th style="text-align: left; padding: 2px;">1/</th> <th style="text-align: center; padding: 2px;">1-2 4-5</th> <th style="text-align: center; padding: 2px;">2-3 5-6</th> <th style="text-align: center; padding: 2px;">2-3 5-6</th> <th style="text-align: center; padding: 2px;">1-2 4-5</th> <th style="text-align: left; padding: 2px;">1/</th> </tr> </thead> <tbody> <tr> <td style="text-align: left; padding: 2px;">MS27790-1</td> <td style="text-align: left; padding: 2px;">MS27790-34</td> <td style="text-align: center; padding: 2px;">ON</td> <td style="text-align: center; padding: 2px;">2-3 ON</td> <td style="text-align: center; padding: 2px;">4-5</td> <td style="text-align: center; padding: 2px;">ON</td> <td style="text-align: left; padding: 2px;"></td> </tr> <tr> <td style="text-align: left; padding: 2px;">-2</td> <td style="text-align: left; padding: 2px;">-35</td> <td style="text-align: center; padding: 2px;">MOM-ON</td> <td style="text-align: center; padding: 2px;">2-3 ON</td> <td style="text-align: center; padding: 2px;">4-5</td> <td style="text-align: center; padding: 2px;">ON</td> <td style="text-align: left; padding: 2px;"></td> </tr> <tr> <td style="text-align: left; padding: 2px;">-3</td> <td style="text-align: left; padding: 2px;">-36</td> <td style="text-align: center; padding: 2px;">MOM-ON</td> <td style="text-align: center; padding: 2px;">2-3 ON</td> <td style="text-align: center; padding: 2px;">4-5</td> <td style="text-align: center; padding: 2px;">MOM-ON</td> <td style="text-align: left; padding: 2px;"></td> </tr> <tr> <td style="text-align: left; padding: 2px;">-4</td> <td style="text-align: left; padding: 2px;">-38</td> <td style="text-align: center; padding: 2px;">ON</td> <td style="text-align: center; padding: 2px;">1-2 ON</td> <td style="text-align: center; padding: 2px;">5-6</td> <td style="text-align: center; padding: 2px;">ON</td> <td style="text-align: left; padding: 2px;"></td> </tr> <tr> <td style="text-align: left; padding: 2px;">-5</td> <td style="text-align: left; padding: 2px;">-39</td> <td style="text-align: center; padding: 2px;">MOM-ON</td> <td style="text-align: center; padding: 2px;">1-2 ON</td> <td style="text-align: center; padding: 2px;">5-6</td> <td style="text-align: center; padding: 2px;">ON</td> <td style="text-align: left; padding: 2px;"></td> </tr> <tr> <td style="text-align: left; padding: 2px;">-6</td> <td style="text-align: left; padding: 2px;">-40</td> <td style="text-align: center; padding: 2px;">MOM-ON</td> <td style="text-align: center; padding: 2px;">1-2 ON</td> <td style="text-align: center; padding: 2px;">5-6</td> <td style="text-align: center; padding: 2px;">MOM-ON</td> <td style="text-align: left; padding: 2px;"></td> </tr> </tbody> </table>						CANCELED MS PART NUMBER	SUBSTITUTE MS PART NUMBER	CIRCUITS MADE WITH TOGGLE LEVER IN				OPPOSITE	KEYING SIDE	CENTER POSITION	KEYING SIDE	OPPOSITE	1/	1/	1-2 4-5	2-3 5-6	2-3 5-6	1-2 4-5	1/	MS27790-1	MS27790-34	ON	2-3 ON	4-5	ON		-2	-35	MOM-ON	2-3 ON	4-5	ON		-3	-36	MOM-ON	2-3 ON	4-5	MOM-ON		-4	-38	ON	1-2 ON	5-6	ON		-5	-39	MOM-ON	1-2 ON	5-6	ON		-6	-40	MOM-ON	1-2 ON	5-6	MOM-ON	
CANCELED MS PART NUMBER	SUBSTITUTE MS PART NUMBER	CIRCUITS MADE WITH TOGGLE LEVER IN						OPPOSITE																																																									
		KEYING SIDE	CENTER POSITION	KEYING SIDE	OPPOSITE																																																												
1/	1/	1-2 4-5	2-3 5-6	2-3 5-6	1-2 4-5	1/																																																											
MS27790-1	MS27790-34	ON	2-3 ON	4-5	ON																																																												
-2	-35	MOM-ON	2-3 ON	4-5	ON																																																												
-3	-36	MOM-ON	2-3 ON	4-5	MOM-ON																																																												
-4	-38	ON	1-2 ON	5-6	ON																																																												
-5	-39	MOM-ON	1-2 ON	5-6	ON																																																												
-6	-40	MOM-ON	1-2 ON	5-6	MOM-ON																																																												
1/ The canceled part numbers are no longer procurable, the substitute part numbers have a lower dielectric withstanding voltage at reduced barometric pressure (see 2 below)																																																																	
NOTES 1 All switches on this standard are designed so that the movement of the switch mechanism is opposite to that of the toggle lever 2 Test voltage for dielectric withstanding voltage at reduced barometric pressure, shall be 400 V rms minimum. 3 Electrical endurance shall be performed for 30,000 cycles. 4 Mechanical endurance shall be performed 50,000 cycles at -65°C and then 50,000 cycles at 85°C. 5 Intermediate current shall be performed for 30,000 cycles. 6 Terminals shall be molded into the switch case and shall accommodate no 16 awg wire 7 Strength of actuating lever pivot and lever stop 8 lbs. 8 Sand and dust. Toggle boots in accordance with MIL-B-5423 shall be used 9 Maximum weight shall be .020 lb. 10 Electrical ratings for 28 volts dc and 115 volts ac at 400 Hz Lamp load = 1 ampere, resistive load = 5 amperes, inductive load = 2 amperes. 11 In the event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence 12 Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DDIIS) specified in the solicitation form a part of this standard to the extent specified herein																																																																	
(1) denotes change																																																																	
PREPARING ACTIVITY: AIR FORCE-85 LUSTUDIANS ANMI: ER NAVY AS AIR FORCE: DLA REVIEW: 01 MAY 1987 APPROVED: 11.29 LIGER: 11.29 PROJECT NUMBER: 11.29		MILITARY SPECIFICATION SHEET TITLE: SWITCH, TOGGLE, MINIATURE, DOUBLE POLE, INSULATED		SPECIFICATION SHEET NUMBER: MS27790D 18 Jun 1989 SUPERSEDING: MS27790-1 20 May 1984 AMSC: N/A FSC: 6444																																																													
DISTRIBUTION STATEMENT: A / 1000 COPIES OF THIS RELEASE ARE RESTRICTED TO APPROVED CONTRACTOR FACILITIES Page 1 of 1																																																																	