

MS PART NO. BALL COLOR COLOR OF DIAL MARKING

(a) MS28024-1 DARK

MS28024-2 WHITE LUSTERLESS WHITE

MS28024-2A WHITE FLUORESCENT

MS28024-3 DARK FLUORESCENT

MS28024-3A DARK LUSTERLESS WHITE

(a)PART NUMBER MS28024-I INACTIVE FOR DESIGN AFTER 8 FEBRUARY 1956

FOR DEFINITION AND APPLICATION OF DRAWING STATUS NOTES SEE MIL-STD- 962.

THE MANUFACTURER SHALL FURNISH SUFFICIENT MOUNTING SREWS NUMBER 6-32UNC-2A ROUND HEAD, BRASS, MACHINE, HAVING DURABLE, DULL BLACK, OXIDIZED OR BLACK NICKEL FINISH. LENGTH SHALL BE SUFFICIENT FOR MOUNTING IN PANEL .375 INCHES THICK.

DIMENSIONS IN INCHES.

CERTAIN PROVISIONS (VOLTAGE AND CASE DIMENSIONS) OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ASCC 10/5 AND STANDARD 3322. WHEN REVISIONS OR CANCELLATION OF THIS STANDARD IS PROPOSED, WHICH WILL AFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRATE RECONCILIATION ACTION THROUGH INTERNATIONAL STANDARDIZATION CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES, IF REQUIRED.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

REFERENCE DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIO.

						•	
P. A	USAF-7I INTERNATION	INDICATORS, TURN AND SLIP, 4-MINUTE TURN,	MILITARY STANDARD				
H	MAUV_AOI	2 3/4 INCH DIAL	MS	28	02	4	
PRO	CUREMENT SPECIFICATION	SUPERSEDES:	SHEET	1	OF	1	

DD . MAY 73 672-1 (COORDINATED)

6610-0183

Apr 88

Ŋ

 \odot

(A) 8 FEB 56 (B) 12 SEPT. 56 (C) 3 APR 58 (D) DEC 65 (E) 15 OCT 68 (E) 18 NOV 69 (B) 31 JULY 73

REMSED

9 NOV 5

APPROVED