



DASH NO.	FIN	ID	D ±.005	R ±.010	S ±.010	W ±.005
335		2.725				
336		2.850				
337		2.975				
338		3.100				
339		3.225				
340		3.350				
341		3.475				
342		3.600	±.015	.375	.093	.078 .210
343		3.725				
344		3.850				
345		3.975				
346		4.100				
347		4.225				
348		4.350				
349		4.475				

DASH NO.	FIN	ID	D ±.005	R ±.010	S ±.010	W ±.006
430		5.100				
431		5.225				
432		5.350				
433		5.475				
434		5.600				
435		5.725				
436		5.850	±.023	.531	.125	.105 .275
437		5.975				
438		6.225				
439		6.475				
440		6.725				
441		6.975				
442		7.225				
443		7.475				
444		7.725				
445		7.975				
446		8.175				
447		8.375				
448		8.575				
449		8.775				
450		10.175				
451		10.975	±.030	.531	.125	.105 .275
452		11.175				
453		11.375				
454		11.575				
455		11.775				
456		11.975				
457		12.175				
458		12.375				
459		12.575				
460		12.775				

DASH NO.	FIN	ID	D ±.005	R ±.010	S ±.010	W ±.006
425		4.475				
426		4.600				
427		4.725	±.015	.531	.125	.105 .275
428		4.850				
429		4.975				

(B)

EXAMPLE OF PART NUMBER: MS28772-340 = PACKING, ID 3.350 INCHES, MATERIAL, CLASS B OF SPECIFICATION MIL-P-5516.

DIMENSIONS IN INCHES

FOR ACCEPTABLE PRODUCTS, SEE QPL-5516.

INSTALLATION DETAILS IN ACCORDANCE WITH STANDARD O-RING PACKINGS, SPECIFICATION MIL-P-5514. GLAND DIMENSIONS IN ACCORDANCE WITH TABLE II, SPECIFICATION MIL-P-5514.

STANDARD O-RING GROOVE FOR O-RING AND BACKUP RINGS WILL ACCOMMODATE D-RING ALONE.

FOR USE IN LANDING GEAR SHOCK STRUT AS ROO SEAL ONLY.

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID

THIS MILITARY STANDARD IS MANDATORY FOR USE BY ALL DEPARTMENTS AND AGENCIES IN THE
 DEPARTMENT OF DEFENSE. SELECTION FOR ALL NEW ENGINEERING AND DESIGN APPLICATIONS AND
 FOR REPETITIVE USE SHALL BE MADE FROM THIS DOCUMENT.

APPROVED 1 Oct 56 REVISED 1 June 67 27 Jan 71

P.A. DMAP - M Other: CMAP DMAP - M Army - AT Navy - AN	<h1>MILITARY STANDARD</h1>		<h1>MS28772</h1>
	PACKING, PREFORMED, ("D" RING, SHOCK STRUT)		
PRECEDENT SPECIFICATION MIL-P-5514	SUPERSEDES:	SHEET 1 OF 1	

80 PERM GPO-I (COORDINATED)
1 SEP 57