

- 1. MATERIAL: SEE PROCUREMENT SPECIFICATION, EXCEPT AS NOTED.
- 2. FINISH: SEE PROCUREMENT SPECIFICATION.
- 3. DIMENSIONS IN INCHES, UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ± .010, ANGLES ± 10.
- 4. CAP MUST MATE WITH FLANGE MS24484-5.
- 5. CAP MUST HAVE DETENT LOCK TO PREVENT ACCIDENTAL DISCONNECTION FROM FLANGE. ROTATION TO LOCK 300±50 CLOCKWISE.
- 6. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
- 7. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
- 8. DIMENSIONS INDICATED BY "MAX" OR "MIN" ARE ENVELOPE DIMENSIONS.
- \* CERTAIN PROVISIONS OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT STANAG NO. 3294. WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED, THE DEPARTMENTAL CUSTODIANS WILL INFORM THEIR RESPECTIVE DEPARTMENTAL STANDARDIZATION OFFICES SO THAT APPROPRIATE ACTION MAY BE TAKEN RESPECTING THE INTERNATIONAL AGREEMENTS CONCERNED.

REVISION LETTERS ARE NOT USED TO DENOTE CHANGES DUE TO THE EXTENSIVENESS OF THE CHANGES.

PREPARING ACTIVITY: NAVY-AS SPECIFICATION SHEET NUMBER MILITARY SPECIFICATION SHEET CUSTODIANS: ARMY- AV NAVY-MS29525F 15 JANUARY 1991 AIR FORCE- 11 DLA-TITLE CAP-PRESSURE FUEL SERVICING. SUPERSEDING REVIEW: MS29525 E NOMINAL 2 1/2 INCH DIAMETER. FLUSH TYPE FSC 1560 AMSC-N/A PROJECT NUMBER: 1560-D186 DISTRIBUTION STATEMENT