

This standard has been approved by the Department of the Navy and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

FED. SUP CLASS <b>5935</b>																																																																																																														
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">SHELL SIZE</th> <th>F</th> <th>G</th> <th>K</th> <th>N</th> <th>R</th> <th>S</th> <th>Y</th> <th>W</th> <th>H</th> </tr> <tr> <th>+ .003 - .001 DIA</th> <th>+ .001 - .016</th> <th>+ 0.7 - .000</th> <th>+ .010 - .011 DIA</th> <th>+ .016</th> <th>MAX</th> <th>THREAD UNEF CLASS 2A</th> <th>7/16 - 28 9/16 - 24 11/16 - 24 13/16 - 20 15/16 - 20 1 1/16 - 18 1 3/16 - 18 1 5/16 - 18 1 7/16 - 18</th> <th>MIN FULL THREAD</th> </tr> </thead> <tbody> <tr> <td>8</td> <td>.322</td> <td></td> <td></td> <td>.500</td> <td></td> <td></td> <td>5/8 - 24</td> <td>7/16 - 28</td> <td></td> </tr> <tr> <td>10</td> <td>.439</td> <td></td> <td>.609</td> <td></td> <td></td> <td>812</td> <td>3/4 - 20</td> <td>9/16 - 24</td> <td>250</td> </tr> <tr> <td>12</td> <td>.564</td> <td>391</td> <td>.734</td> <td></td> <td>094</td> <td></td> <td>7/8 - 20</td> <td>11/16 - 24</td> <td></td> </tr> <tr> <td>14</td> <td>.688</td> <td></td> <td>.859</td> <td></td> <td></td> <td></td> <td>1 - 20</td> <td>13/16 - 20</td> <td></td> </tr> <tr> <td>16</td> <td>.793</td> <td></td> <td>.969</td> <td></td> <td></td> <td></td> <td>1 1/8 - 18</td> <td>15/16 - 20</td> <td></td> </tr> <tr> <td>18</td> <td>.910</td> <td></td> <td>1.109</td> <td></td> <td></td> <td></td> <td>1 1/4 - 18</td> <td>1 1/16 - 18</td> <td></td> </tr> <tr> <td>20</td> <td>1.025</td> <td></td> <td>1.219</td> <td></td> <td></td> <td>906</td> <td>1 5/8 - 18</td> <td>1 3/16 - 18</td> <td></td> </tr> <tr> <td>22</td> <td>1.150</td> <td>422</td> <td>1.344</td> <td></td> <td>175</td> <td></td> <td>1 1/2 - 18</td> <td>1 5/16 - 18</td> <td>312</td> </tr> <tr> <td>24</td> <td>1.275</td> <td></td> <td>1.469</td> <td></td> <td></td> <td>937</td> <td>1 5/8 - 18</td> <td>1 7/16 - 18</td> <td></td> </tr> </tbody> </table>	SHELL SIZE	F	G	K	N	R	S	Y	W	H	+ .003 - .001 DIA	+ .001 - .016	+ 0.7 - .000	+ .010 - .011 DIA	+ .016	MAX	THREAD UNEF CLASS 2A	7/16 - 28 9/16 - 24 11/16 - 24 13/16 - 20 15/16 - 20 1 1/16 - 18 1 3/16 - 18 1 5/16 - 18 1 7/16 - 18	MIN FULL THREAD	8	.322			.500			5/8 - 24	7/16 - 28		10	.439		.609			812	3/4 - 20	9/16 - 24	250	12	.564	391	.734		094		7/8 - 20	11/16 - 24		14	.688		.859				1 - 20	13/16 - 20		16	.793		.969				1 1/8 - 18	15/16 - 20		18	.910		1.109				1 1/4 - 18	1 1/16 - 18		20	1.025		1.219			906	1 5/8 - 18	1 3/16 - 18		22	1.150	422	1.344		175		1 1/2 - 18	1 5/16 - 18	312	24	1.275		1.469			937	1 5/8 - 18	1 7/16 - 18	
SHELL SIZE	F		G	K	N	R	S	Y	W	H																																																																																																				
	+ .003 - .001 DIA	+ .001 - .016	+ 0.7 - .000	+ .010 - .011 DIA	+ .016	MAX	THREAD UNEF CLASS 2A	7/16 - 28 9/16 - 24 11/16 - 24 13/16 - 20 15/16 - 20 1 1/16 - 18 1 3/16 - 18 1 5/16 - 18 1 7/16 - 18	MIN FULL THREAD																																																																																																					
8	.322			.500			5/8 - 24	7/16 - 28																																																																																																						
10	.439		.609			812	3/4 - 20	9/16 - 24	250																																																																																																					
12	.564	391	.734		094		7/8 - 20	11/16 - 24																																																																																																						
14	.688		.859				1 - 20	13/16 - 20																																																																																																						
16	.793		.969				1 1/8 - 18	15/16 - 20																																																																																																						
18	.910		1.109				1 1/4 - 18	1 1/16 - 18																																																																																																						
20	1.025		1.219			906	1 5/8 - 18	1 3/16 - 18																																																																																																						
22	1.150	422	1.344		175		1 1/2 - 18	1 5/16 - 18	312																																																																																																					
24	1.275		1.469			937	1 5/8 - 18	1 7/16 - 18																																																																																																						
(B) INACTIVE FOR DESIGN AFTER 1 JULY 1982. DOCUMENT WILL BE CANCELLED AFTER 1 JULY 1984, USE MIL-C-85049/34.																																																																																																														
(B) DENOTES CHANGES																																																																																																														
P.A. NAVY-AS Other Cust	International Interest	TITLE ADAPTER FOR REAR MOUNTING, JAM NUT, MIL-C-26482 ELECTRIC CONNECTORS	MILITARY STANDARD <b>MS3184(NAVY)</b>																																																																																																											
Procurement Specification			SHEET 1 OF 1																																																																																																											
SUPERSEDES:																																																																																																														

EXAMPLE OF PART NUMBER:  
 MS3184 - 12  
 MS NUMBER      SIZE

NOTES:  
 1. DIMENSIONS IN INCHES  
 2. MATERIAL - ALUMINUM ALLOY  
 3. PLATING - CADMIUM PLATE SPECIFICATION QQ-P-416.  
 TYPE II, CLASS 2  
 4. REMOVE ALL BURRS AND SHARP EDGES  
 5. FOR USE WITH MS3114, MS3124 & MS3474 RECEPTACLES.

APPROVED 25 OCT 1966 REVISED (A) 1 APR 1971 (B) 10 MAY 1982