

This material has been approved by the BUREAU OF AERONAUTICS, WASHINGTON, D.C. for use by the Department of Defense. It is not to be used for any other purpose without the express written permission of the Department of Defense. All other military specifications are required to comply with standard when available.

ENGINE DRIVE PAD		DRIVE RATINGS			ACCESSORY			ACCESSORY ATTACHMENT DATA				ACCESSORY FLANGE DWG. NO.	DRIVE PAD COVER DWG. NO.
MS NO.	DASH NO.	MS3335 SPLINE PITCH DIA., IN.	NOMINAL SPEED, RPM	RATED TORQUE, LB. IN.	RATED POWER, HP	WEIGHT, LB.	STATIC OVERHUNG MOMENT, LB. IN.	ENGINE STUD SPACING AND SIZE	BOLT CIRCLE DIA., IN.	FLANGE CONFIGURATION	V-BAND CLAMPING FLANGE DIA., IN.		
MS3325	-1	0.4583	16,000	150	--	5	15	90° UNJF-3A	2.653	SQUARE	NONE	MS3330	AN100043
	-2	0.4583	4,200	15	--	5	15						
	-1	0.600	12,000	--	6	20	60						
	-2	0.600	12,000	--	12	35	150						
MS3326	-3	0.800	8,000	600	--	25	100	90°	5.000	SQUARE	NONE	MS3331	AN100036
	-4	0.800	16,000	300	--	25	100	.3125-24 UNJF-3A					
	-5	0.600	3,300	750	--	20	80						
	-6	0.800	3,300	1,500	--	35	150						
	-7	0.800	3,300	1,500	--	30	80						
	-8	0.800	3,300	1,500	--	30	80						
	-9	0.800	3,300	1,500	--	30	80						
	-10	0.800	3,300	1,500	--	30	80						
	-11	0.800	3,300	1,500	--	30	80						
	-12	0.800	3,300	1,500	--	30	80						
	-13	0.800	3,300	1,500	--	30	80						
	-14	0.800	3,300	1,500	--	30	80						
	-15	0.800	3,300	1,500	--	30	80						
	-16	0.800	3,300	1,500	--	30	80						
	-17	0.800	3,300	1,500	--	30	80						
	-18	0.800	3,300	1,500	--	30	80						
	-19	0.800	3,300	1,500	--	30	80						
	-20	0.800	3,300	1,500	--	30	80						
	-21	0.800	3,300	1,500	--	30	80						
	-22	0.800	3,300	1,500	--	30	80						
	-23	0.800	3,300	1,500	--	30	80						
	-24	0.800	3,300	1,500	--	30	80						
	-25	0.800	3,300	1,500	--	30	80						
	-26	0.800	3,300	1,500	--	30	80						
	-27	0.800	3,300	1,500	--	30	80						
	-28	0.800	3,300	1,500	--	30	80						
	-29	0.800	3,300	1,500	--	30	80						
	-30	0.800	3,300	1,500	--	30	80						
	-31	0.800	3,300	1,500	--	30	80						
	-32	0.800	3,300	1,500	--	30	80						
	-33	0.800	3,300	1,500	--	30	80						
	-34	0.800	3,300	1,500	--	30	80						
	-35	0.800	3,300	1,500	--	30	80						
	-36	0.800	3,300	1,500	--	30	80						
	-37	0.800	3,300	1,500	--	30	80						
	-38	0.800	3,300	1,500	--	30	80						
	-39	0.800	3,300	1,500	--	30	80						
	-40	0.800	3,300	1,500	--	30	80						
	-41	0.800	3,300	1,500	--	30	80						
	-42	0.800	3,300	1,500	--	30	80						
	-43	0.800	3,300	1,500	--	30	80						
	-44	0.800	3,300	1,500	--	30	80						
	-45	0.800	3,300	1,500	--	30	80						
	-46	0.800	3,300	1,500	--	30	80						
	-47	0.800	3,300	1,500	--	30	80						
	-48	0.800	3,300	1,500	--	30	80						
	-49	0.800	3,300	1,500	--	30	80						
	-50	0.800	3,300	1,500	--	30	80						
	-51	0.800	3,300	1,500	--	30	80						
	-52	0.800	3,300	1,500	--	30	80						
	-53	0.800	3,300	1,500	--	30	80						
	-54	0.800	3,300	1,500	--	30	80						
	-55	0.800	3,300	1,500	--	30	80						
	-56	0.800	3,300	1,500	--	30	80						
	-57	0.800	3,300	1,500	--	30	80						
	-58	0.800	3,300	1,500	--	30	80						
	-59	0.800	3,300	1,500	--	30	80						
	-60	0.800	3,300	1,500	--	30	80						
	-61	0.800	3,300	1,500	--	30	80						
	-62	0.800	3,300	1,500	--	30	80						
	-63	0.800	3,300	1,500	--	30	80						
	-64	0.800	3,300	1,500	--	30	80						
	-65	0.800	3,300	1,500	--	30	80						
	-66	0.800	3,300	1,500	--	30	80						
	-67	0.800	3,300	1,500	--	30	80						
	-68	0.800	3,300	1,500	--	30	80						
	-69	0.800	3,300	1,500	--	30	80						
	-70	0.800	3,300	1,500	--	30	80						
	-71	0.800	3,300	1,500	--	30	80						
	-72	0.800	3,300	1,500	--	30	80						
	-73	0.800	3,300	1,500	--	30	80						
	-74	0.800	3,300	1,500	--	30	80						
	-75	0.800	3,300	1,500	--	30	80						
	-76	0.800	3,300	1,500	--	30	80						
	-77	0.800	3,300	1,500	--	30	80						
	-78	0.800	3,300	1,500	--	30	80						
	-79	0.800	3,300	1,500	--	30	80						
	-80	0.800	3,300	1,500	--	30	80						
	-81	0.800	3,300	1,500	--	30	80						
	-82	0.800	3,300	1,500	--	30	80						
	-83	0.800	3,300	1,500	--	30	80						
	-84	0.800	3,300	1,500	--	30	80						
	-85	0.800	3,300	1,500	--	30	80						
	-86	0.800	3,300	1,500	--	30	80						
	-87	0.800	3,300	1,500	--	30	80						
	-88	0.800	3,300	1,500	--	30	80						
	-89	0.800	3,300	1,500	--	30	80						
	-90	0.800	3,300	1,500	--	30	80						
	-91	0.800	3,300	1,500	--	30	80						
	-92	0.800	3,300	1,500	--	30	80						
	-93	0.800	3,300	1,500	--	30	80						
	-94	0.800	3,300	1,500	--	30	80						
	-95	0.800	3,300	1,500	--	30	80						
	-96	0.800	3,300	1,500	--	30	80						
	-97	0.800	3,300	1,500	--	30	80						
	-98	0.800	3,300	1,500	--	30	80						
	-99	0.800	3,300	1,500	--	30	80						
	-100	0.800	3,300	1,500	--	30	80						
	-101	0.800	3,300	1,500	--	30	80						
	-102	0.800	3,300	1,500	--	30	80						
	-103	0.800	3,300	1,500	--	30	80						
	-104	0.800	3,300	1,500	--	30	80						
	-105	0.800	3,300	1,500	--	30	80						
	-106	0.800	3,300	1,500	--	30	80						
	-107	0.800	3,300	1,500	--	30	80						
	-108	0.800	3,300	1,500	--	30	80						
	-109	0.800	3,300	1,500	--	30	80						
	-110	0.800	3,300	1,500	--	30	80						
	-111	0.800	3,300	1,500	--	30	80						

