

NOTICE: REVIEW/USER INFORMATION IS CURRENT AS OF THE DATE OF THIS DOCUMENT FOR FUTURE COMBINATION OF CHANGES TO THIS DOCUMENT. DRAFT CIRCULATION SHOULD BE BASED ON THE INFORMATION IN THE CURRENT EDITIONS.

REVISER - 11
AIR FORCE - 11
ARMY - MR
NAVY - AS

DS22

This military standard is approved by the Department of Defense and is mandatory for use by all Departments & Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

FED. SUP CLASS 5330																																																									
<p>ALL DIAMETERS OF CROSS SECTION SHALL EQUAL W (SEE NOTE 3)</p> <p>SECTION A-A</p> <p>DETAIL B ENLARGED</p>																																																									
<table border="1"> <thead> <tr> <th>DASH NO.</th> <th>TUBING SIZE OD(a)</th> <th>W DIA</th> <th>B ID</th> </tr> </thead> <tbody> <tr> <td>-2</td> <td>1/8</td> <td>.064</td> <td>.239</td> </tr> <tr> <td>-3</td> <td>3/16</td> <td>.072</td> <td>.301</td> </tr> <tr> <td>-4</td> <td>1/4</td> <td>.078</td> <td>.351</td> </tr> <tr> <td>-5</td> <td>5/16</td> <td>.087</td> <td>.414</td> </tr> <tr> <td>-6</td> <td>3/8</td> <td>.097</td> <td>.468</td> </tr> <tr> <td>-8</td> <td>1/2</td> <td>.116</td> <td>.644</td> </tr> <tr> <td>-10</td> <td>5/8</td> <td>.116</td> <td>.755</td> </tr> <tr> <td>-12</td> <td>3/4</td> <td>.118</td> <td>.924</td> </tr> <tr> <td>-16</td> <td>1</td> <td>.118</td> <td>1.171</td> </tr> <tr> <td>-20</td> <td>1 1/4</td> <td>.118</td> <td>1.475</td> </tr> <tr> <td>-24</td> <td>1 1/2</td> <td>.118</td> <td>1.720</td> </tr> <tr> <td>-28</td> <td>1 3/4</td> <td>.118</td> <td>2.090</td> </tr> <tr> <td>-32</td> <td>2</td> <td>.118</td> <td>2.337</td> </tr> </tbody> </table> <p>(a) SEE AND10064 SHEET NOS. 2 AND 3 FOR INSTALLATION DETAILS ON TUBE FITTINGS.</p> <p>NOTES.</p> <ol style="list-style-type: none"> 1 - MATERIAL - SEE PROCUREMENT SPECIFICATION. 2 - DIMENSIONS IN INCHES. 3 - RINGS MAY BE OFF REGISTER DUE TO MOLD MISALIGNMENT WITHIN TOLERANCES OF W DIMENSION. PROVIDED ALL CROSS-SECTIONAL DIAMETERS, INCLUDING THE PROTRUSIONS (FLASH EXCLUDED) OF BOTH HALVES WHERE APPLICABLE, SATISFY THE W DIMENSION WITH TOLERANCE. <p>* CERTAIN PROVISIONS OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT (ASCC AIR STD 17/21 PIPE FITTING SEALING RINGS). WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED, WHICH WILL EFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRIATE RECONCILIATION ACTION THROUGH INTERNATIONAL STANDARDIZATION CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES, IF REQUIRED "</p> <p>FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.</p> <p>REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</p>		DASH NO.	TUBING SIZE OD(a)	W DIA	B ID	-2	1/8	.064	.239	-3	3/16	.072	.301	-4	1/4	.078	.351	-5	5/16	.087	.414	-6	3/8	.097	.468	-8	1/2	.116	.644	-10	5/8	.116	.755	-12	3/4	.118	.924	-16	1	.118	1.171	-20	1 1/4	.118	1.475	-24	1 1/2	.118	1.720	-28	1 3/4	.118	2.090	-32	2	.118	2.337
DASH NO.	TUBING SIZE OD(a)	W DIA	B ID																																																						
-2	1/8	.064	.239																																																						
-3	3/16	.072	.301																																																						
-4	1/4	.078	.351																																																						
-5	5/16	.087	.414																																																						
-6	3/8	.097	.468																																																						
-8	1/2	.116	.644																																																						
-10	5/8	.116	.755																																																						
-12	3/4	.118	.924																																																						
-16	1	.118	1.171																																																						
-20	1 1/4	.118	1.475																																																						
-24	1 1/2	.118	1.720																																																						
-28	1 3/4	.118	2.090																																																						
-32	2	.118	2.337																																																						
<table border="1"> <thead> <tr> <th>P.A. NAVY-AS</th> <th>INTERNATIONAL INTEREST</th> <th>TITLE</th> <th>MILITARY STANDARD</th> </tr> </thead> <tbody> <tr> <td>Other Cont</td> <td>*</td> <td>PACKING, PREFORMED, STRAIGHT THREAD TUBE FITTING BOSS, HYDRAULIC, -65°F 10+275°F</td> <td>MS3393</td> </tr> <tr> <td>AIR FORCE-11</td> <td></td> <td></td> <td></td> </tr> <tr> <td>ARMY-MR</td> <td></td> <td></td> <td></td> </tr> <tr> <td>PROCUREMENT SPECIFICATION</td> <td>SUPERSEDES</td> <td></td> <td></td> </tr> <tr> <td>MIL-P-81716</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="3">SHEET 1 OF 1</td> <td></td> </tr> </tbody> </table>		P.A. NAVY-AS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD	Other Cont	*	PACKING, PREFORMED, STRAIGHT THREAD TUBE FITTING BOSS, HYDRAULIC, -65°F 10+275°F	MS3393	AIR FORCE-11				ARMY-MR				PROCUREMENT SPECIFICATION	SUPERSEDES			MIL-P-81716				SHEET 1 OF 1																															
P.A. NAVY-AS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD																																																						
Other Cont	*	PACKING, PREFORMED, STRAIGHT THREAD TUBE FITTING BOSS, HYDRAULIC, -65°F 10+275°F	MS3393																																																						
AIR FORCE-11																																																									
ARMY-MR																																																									
PROCUREMENT SPECIFICATION	SUPERSEDES																																																								
MIL-P-81716																																																									
SHEET 1 OF 1																																																									

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PLATE FO 14330

APPROVED 14 FEB 1969 REVISED