

USER SYMBOLS:

REVIEWER SYMBOLS:

"Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current D00155."

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

DASH NO.		A ±.100
TYPE I REUSABLE	TYPE II REUSABLE AND REFILLABLE	
-1A	-11	1.062
-2	-12	.474

THREADS TO PROVIDE A SATISFACTORY FIT IN A 14-1.25 MM THREADED BOSS HAVING

PITCH DIA MAX .5232
MIN .5202

MINOR DIA MAX .5000
MIN .4942

MAJOR DIA MIN .5522

GASKET
.094^{+.000}_{-.020}

.810 MAX DIA

.470 MAX DIA

.850 MAX DIA

.250 MIN

.500 MIN

.094^{+.010}_{-.000} UNTHREADED

.120 MAX RAD

.807^{+.000}_{-.010}

.320 ±.010

2.312^{+.125}_{-.000}

CABLE PROTECTOR AN4060-1 REF

TOP OF PLUG TO BE SO CONSTRUCTED TO PROVIDE A SNAP AND SECURE FIT FOR THE CABLE PROTECTOR, AND ALLOW IT A CIRCULAR MOVEMENT OF 15° ABOUT THE LONGITUDINAL AXIS OF THE PLUG

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

P.A. NAVY - AS Other Cast AF-82 ARMY-ME	TITLE PLUG, DEHYDRATOR, HUMIDITY INDICATING, ENGINE CYLINDER, 14 MM THREAD	MILITARY STANDARD MS3396
PROCUREMENT SPECIFICATION MIL-I-6131	SUPERSEDES: AN4064	SHEET 1 OF 1

DD FORM 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 17709

REVISED
APPROVED 1, Jul 62