


SECTIONAL VIEW OF DETAIL

	A	B	C	D
DASH NUMBER	+.0000 -.0005	+.0002 -.0000	+.0000 -.0002	D (RAD)
-22	.0330	.0600	.0480	.003 .006
-20	.0440	.0745	.0615	.003 .006
-16	.0660	.1065	.0925	.005 .010

GAGE FOR CONTACT RETENTION TESTS.

- NOTES:
1. DIMENSIONS ARE IN INCHES.
  2. MATERIAL: HARDENED TOOL STEEL.
  3. FINISH: 32 MICROINCH POLISHED.
  4. EXAMPLE OF PART NUMBER:



5. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
6. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

NOTE: APPROVAL OF THIS FINAL DRAFT IS SUBJECT TO PREPARING ACTIVITY REVIEW. DO NOT USE FOR PROCUREMENT PURPOSES.

ⓑ Entire standard revised

P.A Navy - AS	International Interest	TITLE TEST GAGE, MIL-C-26482 SERIES 2 (CLASS N), MIL-C-81703 SERIES 3 (CLASS N) AND MIL-C-0081511 SERIES 3 AND 4 (CLASS L) CONTACT RETENTION FEATURE	MILITARY STANDARD
Other Cust Army - EL AF - 85			<b>MS 3462</b>
Procurement Specification		SUPERSEDES: <b>MS3462 (NAVY)</b>	<b>SHEET 1 OF 1</b>

DD FORM 1 SEP 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

5935-1947-35

User activities: Army, AV, Navy, Air Force

Activities: Army MU, MI, EL, Navy EC, SH, Air Force 11, 17

This standard is approved for use by all Departments and Agencies of the Department of Defense in connection with all new engineering and design applications and for repetitive use (if) be made from this document.

APPROVED 1 Apr 71 REVISED A 18 Oct 71 ⓑ 5 SEPT 1975