

INCH-POUND

MS33736D
 20 November 2002
 SUPERSEDING
 MS33736C
 13 November 1991

DETAIL SPECIFICATION SHEET

TURNBUCKLE ASSEMBLIES, CLIP LOCKING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-8878 and QPL-8878 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.




FIGURE 1. Clip locking of turnbuckle assemblies.

MS33736D

TABLE I. Dimensions and dash numbers.

Wire rope diameter reference	Thread UNF-3B	Locking clip MS21256 <u>1/</u>	Turnbuckle body MS21251
1/16	0.1380 (#6)-40	-1	-2S
		-2	-2L
3/32	0.1900 (#10)-32	-1	-3S
		-2	-3L
5/32	0.2500 (1/4)-28	-1	-5S
		-2	-5L
3/16	0.3125 (5/16)-24	-1	-6S
		-2	-6L
1/4	0.3750 (3/8)-24	-2	-8L
9/32	0.4375 (7/16)-20	-3	-9L
5/16	0.5000 (1/2)-20		-10L

1/ Two locking clips needed for each turnbuckle.

NOTES:

1. Prior to safetying, both threaded terminals shall be screwed an equal distance into the turnbuckle body and shall be screwed in at least so far that not more than three full threads of any terminal are exposed outside the body.

2. After the turnbuckle has been adjusted to its locking position, with the slot indicator groove on the terminals and slot indicator notch on body aligned, insert the end of the locking clip into the terminal body, as illustrated in figure 1, until the U curved end of the locking clip is over the hole in the center of the body. Press the locking clip into the hole to its full extent. The curved end of the locking clip will expand and latch in the body slot. To check proper seating of the locking clip, attempt to remove pressed U end from body hole with fingers only. (Do not use tools as locking clip could become distorted.)

3. Locking clips are for one time use only and shall not be reused.

4. Both locking clips may be inserted in the same hole of the turnbuckle body or in opposite holes.

5. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence.

6. Unless otherwise specified, issues of referenced documents are those in effect at the time of solicitation.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

MS33736D

Custodians:

Army - AV

Navy - AS

Air Force - 99

Preparing Activity:

DLA - GS5

(Project 1560-0025)

Review Activity:

Navy - MC