

REVIEWER: W, IS
USER: AS, AT, MC, ME, CS, SH, WV, YD

FED SUP CLASS
5305

TABLE 1

NOMINAL SIZE		.086	.112	.138	.164	.190	.250	.3125	.375
THREADS PER INCH, UNF-2A		64	48	40	36	32	24	24	24
D BODY DIAMETER	MAX MIN	.0860 .0733	.1120 .0954	.1380 .1194	.1640 .1424	.1900 .1658	.2500 .2225	.3125 .2806	.3750 .3430
A HEAD DIAMETER	MAX MIN	.140 .124	.183 .166	.226 .209	.270 .250	.313 .292	.414 .390	.518 .490	.622 .590
H HEAD SIDE HEIGHT	MAX MIN	.062 .055	.079 .072	.096 .089	.113 .106	.130 .123	.170 .163	.211 .201	.253 .242
O TOTAL HEAD HEIGHT	MAX MIN	.083 .070	.107 .094	.132 .114	.156 .143	.180 .165	.237 .219	.295 .276	.355 .333
J SLOT WIDTH	MAX MIN	.031 .023	.039 .033	.048 .039	.054 .045	.060 .050	.075 .064	.094 .072	.094 .081
T SLOT DEPTH	MAX MIN	.030 .022	.036 .030	.045 .035	.065 .054	.075 .064	.102 .087	.130 .110	.154 .134
E DRILL LOCATION	NOM	.026	.035	.043	.043	.043	.062	.078	.094
F DRILLED HOLE DIA	NOM	.031	.037	.046	.046	.046	.062	.070	.070
R RADIUS	MAX	.015	.017	.021	.025	.028	.036	.047	.056
TENSILE STRENGTH, LBS-MIN		240	400	620	900	1,240	2,250	3,600	5,430
L LENGTH	TOLERANCE	DASH NO. 1	DASH NO. 2	DASH NO. 3	DASH NO. 4	DASH NO. 5	DASH NO. 6	DASH NO. 7	DASH NO. 8
.12	+.00 -.03	1	11	24	39	58			
.19		2	12	25	40	59			
.25		3	13	26	41	60			
.31		4	14	27	42	61	76		
.38		5	15	28	43	62	77	92	
.44	+.00 -.03	6	16	29	44	63	78	93	
.50		7	17	30	45	64	79	94	107
.56		8	18	31	46	65	80	95	108
.62		9	19	32	47	66	81	96	109
.75		10	20	33	48	67	82	97	110
.84	+.00 -.06	21	21	34	49	68	83	98	111
1.00		22	22	35	50	69	84	99	112
1.25		23	23	36	51	70	85	100	113
1.50		24	24	37	52	71	86	101	114
1.75		25	25	38	53	72	87	102	115
2.00	+.00 -.09	26	26	39	54	73	88	103	116
2.25		27	27	40	55	74	89	104	117
2.50		28	28	41	56	75	90	105	118
2.75		29	29	42	57	76	91	106	119
3.00		30	30	43	58	77	92		

(B) * Dash numbers 1 thru 57 are INACTIVE FOR NEW DESIGN AFTER 6 March 1974.

(H) FOR CHANGES SEE SHEETS 1 AND 2.

P.A. NO. Other Cost A2	TITLE SCREW, MACHINE-DRILLED FILLISTER HEAD, SLOTTED, ALUMINUM ALLOY, UNF-2A	MILITARY STANDARD MS 35278
PROCUREMENT SPECIFICATION FF-N-92	SUPersedes MS35161 in part; MS35166 in part	SHEET 1 OF 2

DD FORM 672-1 (COORDINATED)

APPROVED 9 FEB 1954 REVISED (A) 18 JUN 1962 (B) 6 MAR 1974

FED. SUP CLASS
5305

NOTES:

- (B) 1. **MATERIAL:** Aluminum alloy, 2024, in accordance with QQ-A-200/3 or QQ-A-225/6. The minimum ultimate tensile strength shall be 62,000 PSI.
2. **PROTECTIVE COATING:** Anodized in accordance with MIL-A-8625, Type I or II, Class 1.
3. **THREADS:** The threads shall be in accordance with Screw-Thread Standards for Federal Services, Handbook M28.
4. **DIMENSIONS:** All dimensions in Table I are in inches.
5. **PART NUMBER:** The MS part number consists of the MS number, plus the dash number.
Example: MS35278-58.
- (B) 6. **THREAD LENGTH:** Full form threads shall extend to within 2 threads or less of head bearing surface for lengths thru 2.00 inches/50.80 millimetres. Longer lengths shall have a minimum full form thread length of 1.50 inches/38.10 millimetres.
7. The drilled hole shall be approximately at a right angle to the slot and may be permitted to break through the bottom of the slot. All burrs and sharp edges shall be removed.
8. Referenced documents shall be of the issue in effect on date of invitations for bid.
9. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

(B) TABLE II
METRIC TRANSLATION OF TABLE I

NOMINAL SIZE		2.18	2.94	3.31	4.17	4.83	6.35	7.94	9.52
THREAD PITCH		.40	.53	.64	.71	.79	.91	1.06	1.06
D BODY DIAMETER	MAX MIN	2.18 1.86	2.84 2.42	3.31 3.01	4.17 3.62	4.83 4.21	6.35 5.65	7.94 7.13	9.52 8.71
A HEAD DIAMETER	MAX MIN	3.56 3.15	4.65 4.22	5.74 5.28	6.86 6.35	7.95 7.42	10.52 9.88	13.16 12.45	15.80 14.99
H HEAD SIDE HEIGHT	MAX MIN	1.57 1.40	2.01 1.83	2.44 2.26	2.87 2.69	3.30 3.12	4.32 4.09	5.36 5.13	6.43 6.15
C TOTAL HEAD HEIGHT	MAX MIN	2.11 1.78	2.72 2.39	3.33 3.00	3.96 3.58	4.57 4.19	6.02 5.56	7.49 7.01	9.02 8.46
J SLOT WIDTH	MAX MIN	.79 .58	.99 .79	1.22 .99	1.37 1.14	1.52 1.27	1.90 1.63	2.13 1.83	2.39 2.06
T SLOT DEPTH	MAX MIN	.76 .56	.97 .76	1.14 .89	1.65 1.37	1.90 1.63	2.59 2.21	3.30 2.79	3.91 3.40
E DRILL LOCATION	NOM	.66	.89	1.09	1.09	1.09	1.57	1.98	2.39
F DRILLED HOLE DIA	NOM	.79	.94	1.17	1.17	1.17	1.57	1.78	1.78
R RADIUS	MAX	.33	.43	.53	.64	.71	.97	1.19	1.42
L LENGTH	TOLERANCE	DASH NO.*	DASH NO.*	DASH NO.*	DASH NO.*	DASH NO.	DASH NO.	DASH NO.	DASH NO.
3.05		1	11	24	39				
4.83		2	12	25	40	56			
6.35		3	13	26	41	59			
7.97		4	14	27	42	60	76		
9.65	+.00	5	15	28	43	61	77	92	
11.18	-.76	6	16	29	44	62	78	93	
12.70		7	17	30	45	63	79	94	107
15.75		8	18	31	46	64	80	95	108
19.05		9	19	32	47	65	81	96	109
22.35		10	20	33	48	66	82	97	110
25.40		11	21	34	49	67	83	98	111
31.75	+.00	22	35	50	68	84	99	112	
38.10	-1.52	23	36	51	69	85	100	113	
44.45			37	52	70	86	101	114	
50.80			38	53	71	87	102	115	
57.15	+.00			54	72	88	103	116	
63.50	-2.29			55	73	89	104	117	
69.85				56	74	90	105	118	
76.20				57	75	91	106	119	

* Dash numbers 1 thru 57 are
INACTIVE FOR NEW DESIGN AFTER 6 March 1974.

P.A. VC Other Code 82	TITLE SCREW, MACHINE-DRILLED FILLISTER HEAD, SLOTTED, ALUMINUM ALLOY, UNF-24	MILITARY STANDARD MS 35278
PROCUREMENT SPECIFICATION FF-S-92	SUPERSEDES: MS35361 in part; MS35366 in part	SHEET 2 OF 2

DD FORM 672-1 (Continued)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

APPROVED 9 FEB 1954 REVISED (A) 18 JUN 1962 (B) FOR CHANGES SEE SHEETS 1 AND 2.

This military standard is approved for use by all new engineering and design applications and for repetitive use shall be made from this document.

REVIEWER: AV, IS
USAR: AS, AT, MC, ME, NS, SH, WV, YD

FOLD

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD - 314



Commander
Rock Island Arsenal
ATTN: SARRI-LE-SC
Rock Island, Illinois 61201

FOLD

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL		OMB Approval No. 22-R255
<p>INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document by DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product or service described in the document. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.</p>		
<p>DOCUMENT IDENTIFIER AND TITLE MS3527- Rev B, Screw, Machine-Drilled Fillister Head, Slotted, Aluminum Alloy, UNF-2A</p>		
<p>NAME OF ORGANIZATION AND ADDRESS</p>		<p>CONTRACT NUMBER</p>
		<p>MATERIAL PROCURED UNDER A</p> <p><input type="checkbox"/> DIRECT GOVERNMENT CONTRACT <input type="checkbox"/> SUBCONTRACT</p>
<p>1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?</p> <p>A. GIVE PARAGRAPH NUMBER AND WORDING.</p> <p>B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES</p>		
<p>2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID</p>		
<p>3. IS THE DOCUMENT RESTRICTIVE?</p> <p><input type="checkbox"/> YES <input type="checkbox"/> NO (If "Yes", in what way?)</p>		
<p>4. REMARKS</p>		
<p>SUBMITTED BY (Printed or typed name and address - Optional)</p>		<p>TELEPHONE NO.</p>
		<p>DATE</p>