

FED. SUP. CLASS
8040

MS PART NO.	FIIN	COLOR	QUANTITY	CHARACTERISTICS
MS 35619-1	597-0884	WHITE	2 OZ STICK	APPLIED BY RUBBING SOLID STICK AGAINST EDGE OF OPTICAL ELEMENT.
				DESCRIPTION: A SOLID, PREPARED FROM OLEORESIN EXUDED BY THE BALSAM FIR. IT HAS EX- CELLENT TRANSPARENCY.

Ⓐ CANCELLED AFTER 16 SEP 65. USE MIL-B-3469 (SEE MSS 8040-1, INDEX NO. 50)

- NOTES: 1. USED FOR CEMENTING OPTICAL ELEMENTS IN PLACE.
2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

THIS DOCUMENT HAS BEEN PROMULGATED BY THE DEPARTMENT OF THE ARMY AS THE MILITARY STANDARD TO LIMIT THE SELECTION OF THE ITEM, PRODUCT, OR DESIGN COVERED HEREIN IN ENGINEERING, DESIGN, AND PROCUREMENT. THIS STANDARD SHALL BECOME EFFECTIVE NOT LATER THAN 90 DAYS AFTER THE LATEST DATE OF APPROVAL SHOWN.

CUSTODIANS CE	OTHER INT. A-CMOQSigt	MILITARY STANDARD	MS35619(CE)
	N- AF(MED SER)		
PROCUREMENT SPECIFICATION MIL-B-3469		SUPERSEDES:	SHEET 1 OF 1